



Switch TP-LINK Rack 8x10Base- T 100Base-TX 1000Base-T TL- SG1008



Modelis: TL-SG1008

Gamintojas: TP-LINK

EAN: 6935364020019

Prekės kodas: 68410

44.00€

What This Product Does

The TL-SG1008 8-Port Gigabit desktop/rack-mount switch provides an easy way to make the transition to Gigabit Ethernet. All 8 ports support auto MDI/MDIX, no need to worry about the cable type, simply plug and play. Moreover, with the innovative energy-efficient technology, the TL-SG1008 can save the power consumption, making it an eco-friendly solution for your business network.

TP-LINK Green Technology

This new generation The 8-Port Gigabit Desktop/Rackmount Switch TL-SG1008 features the latest innovative energy-efficient technologies that can greatly expand your network capacity with much less power. It automatically adjusts power consumption according to the link status and cable length

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

to limit the carbon footprint of your network. It also complies with the EU'S RoHS, prohibiting the use of certain hazardous materials. Besides, 80% of the packaging material can be recycled.

High Performance

The TL-SG1008 features non-blocking wire-speed architecture with a 16Gbps switching capacity for maximum data throughput. An 4K MAC address table provides scalability for even the largest networks. It also supports 802.3x Flow Control for full-duplex mode, and back pressure flow control for half-duplex mode alleviates traffic congestion and ensures reliable data transmission.

Ease to Use

The auto features of this gigabit switch make installation plug and play and hassle-free. No configuring is required. Auto MDI/MDI-X crossover on all ports eliminate the need for crossover cables or uplink ports. Auto-negotiation on each port senses the link speed of a network device (either 10, 100 or 1000 Mbps) and intelligently adjusts for compatibility and optimal performance. Compact size shell make it ideal for desktops with limited space while it is also rackmountable, convenient and safe. Dynamic LED lights provide real-time work status display and basic fault diagnosis. TL-SG1008 features the latest innovative energy-efficient technologies that can greatly expand your network capacity with much less power. It automatically adjusts power consumption according to the link status and cable length to limit the carbon footprint of your network. It also complies with the EU'S RoHS, prohibiting the use of certain hazardous materials. Besides, 80% of the packaging material can be recycled.

- 8 10/100/1000Mbps RJ45 ports
- Supports MAC address auto-learning and auto-aging and auto MDI/MDIX
- Standard 13-inch rackmount steel case
- 802.1p/DSCP QoS enable smooth latency-sensitive traffic

Summary: TP-Link 8-Port Gigabit Desktop/Rackmount Network Switch. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8. Full duplex. MAC address table: 4000 entries, Switching capacity: 16 Gbit/s. Networking standards: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Rack mounting, Form factor: 1U | Vendor Homepage: <https://www.tp-link.com/uk/service-provider/unmanaged-switch/tl-sg1008/> | Switch type: Unmanaged | Basic switching RJ-45 Ethernet ports quantity: 8 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | 10G

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

support: No | Auto MDI/MDI-X: Yes | Auto-negotiation: Yes | Copper ethernet cabling technology: 1000BASE-T/100BASE-TX/10BASE-T | Flow control support: Yes | Full duplex: Yes | Networking standards: IEEE 802.1p/IEEE 802.3/IEEE 802.3ab/IEEE 802.3u/IEEE 802.3x | Jumbo frames: 16000 | Jumbo frames support: Yes | MAC address table: 4000 | Maximum data transfer rate: 1 | Store-and-forward: Yes | Supported data transfer rates: 10/100/1000 Mbps | Switching capacity: 16 | Supported network protocols: CSMA/CD, TCP/IP | Form factor: 1U | LED indicators: Yes | Product colour: Black | Rack mounting: Yes | AC input frequency: 50 - 60 | AC input voltage: 100 - 240 | Power consumption (typical): 4.3 | Power source: AC | Power supply included: Yes | Power over Ethernet (PoE): No | Bandwidth: 16 | Connectivity LEDs: Y | Connectivity technology: Wired | Dimensions (W x D x H) (imperial): 9.8 x 6.2 x 1.7 | Dimensions (WxDxH): 294 x 180 x 44 | Input frequency: 50 - 60 | Networking features: Gigabit Ethernet | Heat dissipation: 14.67 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 40 | Operating temperature (T-T): 32 - 104 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -40 - 70 | Depth: 180 | Height: 44 | Width: 294 | Cables included: AC | Quick start guide: Yes | Package depth: 250 | Package height: 80 | Package type: Box | Package weight: 1700 | Package width: 400 | Certification: FCC, CE, RoHS | Harmonized System (HS) code: 85176990 | Units per Shipping Box: 8 | Unit Calculated Volume: 0.01026 | Unit Calculated Weight: 2.06

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903