



Switch TP-LINK TL-SF1006P Desktop/pedestal 6x10Base-T 100Base-TX PoE+ ports 4 TL- SF1006P



Modelis: TL-SF1006P

Gamintojas: TP-LINK

EAN: 6935364030933

Prekės kodas: 68428

37.99€

Professional High-Power Switch with 4 PoE+ Ports

Plug and Play, with PoE Transmission for Surveillance up to 250 m

Dedicated 4-Port PoE+ Switch (67 W Budget) for Numerous Applications

Compliance with the 802.3af/at PoE standard supports up to 15.4 W on each PoE port. The total 41 W PoE power budget* for the 4× PoE ports opens up a wide range of applications, such as surveillance for offices, dormitories, and small businesses. It is fully compatible with IP cameras, access points, IP phones, computers, printers, and more.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Ideal for IP Surveillance—Up to 250 m Transmissions

With extend mode, the PoE transmission distance reaches up to 250 m**—perfect for IP Camera deployment in large areas.

**The speed of the ports in extend mode will downgrade to 10 Mbps. The actual transmission distance may vary due to power consumption of PoE-powered devices or the cable quality and type.

Priority Video Quality Guaranteed

Quality of sensitive applications like video monitoring in critical business areas is guaranteed by offering higher priority options for ports 1-2 when one-touch Priority Mode is on.

Intelligent Power Management

When total power consumption exceeds 67 W, the intelligent power management will cut the lower priority port power. This ensures the high priority port's power supply and protects the device from power overload. It also automatically detects and provides the required power for your PoE devices while protecting your PoE and non-PoE equipment from being damaged.

Durable Metal Casing

The interior components of TL-SF1006P are protected by high-quality metal casing to ensure a long product life. Having passed an array of stringent reliability tests, TL-SF1006P delivers switching performance you can depend on. Long Description: TP-Link TL-SF1006P. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100), Basic switching RJ-45 Ethernet ports quantity: 6. Full duplex. MAC address table: 2000 entries, Switching capacity: 1.2 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3at. DC input voltage: 53.5 V. Power over Ethernet (PoE) | Vendor Homepage: <https://www.tp-link.com/uk/business-networking/poe-switch/tl-sf1006p/#overview> | Bullet Points:

- 6× 10/100 Mbps RJ45 ports
- 4× PoE+ ports transfer data and power on individual cables
- Works with IEEE 802.3af/at compliant PDs
- Up to 250m data and power transmitting range under Extend Mode**
- Priority Mode ensures high priority of ports 1-2 to guarantee the quality of sensitive application
- Supports PoE Power up to 30 W for each PoE port
- Supports PoE Power up to 67 W for all PoE ports*
- Plug and play with no configuration required

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

| Rack mounting: No | Networking standards: IEEE 802.3af/IEEE 802.3at | 10G support: No | Model name: TL-SF1006P | Power source: DC/PoE | Power supply included: Yes | Switch type: Unmanaged | AC input voltage: 220 | AC input frequency: 50 | DC input voltage: 53.5 | Input current: 1.31 | Stackable: No | Compliance certificates: CE/Federal Communications Commission (FCC)/RoHS | Basic switching RJ-45 Ethernet ports quantity: 6 | Copper ethernet cabling technology: 100BASE-T/100BASE-TX/10BASE-T | Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100) | Power over Ethernet (PoE): Yes | Product colour: Black | Switching capacity: 1.2 | Power consumption (max): 74 | Housing material: Metal | Forwarding rate: 0.8928 | MAC address table: 2000 | Store-and-forward: Yes | LED indicators: Yes | Cable types supported: Cat3/Cat4/Cat5/Cat5e | Power over Ethernet plus (PoE+) ports quantity: 4 | Width: 158 | Operating temperature (T-T): 0 - 40 | Storage temperature (T-T): -40 - 70 | Operating relative humidity (H-H): 10 - 90 | Storage relative humidity (H-H): 5 - 90 | Depth: 101 | Height: 25 | Jumbo frames support: Yes | Jumbo frames: 2000 | Full duplex: Yes | Half duplex: Yes | Sustainability compliance: Yes | AC adapter included: Yes | Package type: Box | User guide: Yes | Total Power over Ethernet (PoE) budget: 67 | Auto MDI/MDI-X: Yes | Auto-negotiation: Yes | Flow control support: Yes | MAC address auto-aging supported: Yes | MAC address auto-learning supported: Yes | Heat dissipation: 252.34 | Package width: 131 | Package depth: 196 | Package height: 121 | Fanless: Yes | Package weight: 870 | Harmonized System (HS) code: 85176990 | Certification: FCC, CE, RoHS | Units per Shipping Box: 12 | Unit Calculated Volume: 0.003959 | Unit Calculated Weight: 0.933

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903