

Yealink MP52 cEdition

Gamintojas: **YEALINK** · Modelis: **MP52-TEAMS** · EAN: **6938818307261** · Prekės kodas: **684402**



217,90 €

Kaina su PVM

Be PVM: **180,08 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Android 9.0
- ✓ 2.4 inch (320 x 240) Non-touch Color Screen
- ✓ Optimal HD audio, Yealink Noise Proof Technology
- ✓ Magnet Handset
- ✓ Bluetooth Headset via Dongle BT41
- ✓ Wi-Fi via Dongle WF50
- ✓ USB Type A port, Supports USB Headset
- ✓ Microsoft Teams-tailored APP
- ✓ Dual-port 10/100M Ethernet Switch, Supports PoE
- ✓ Supports Microsoft/Yealink/Unify Square Device Management Platform



Aprašymas

Microsoft Phone MP52

A cost-effective basic Teams phone with high performance, Android 9.0 OS-based Yealink MP52 is plentiful in practical functions and outstanding in calling experience. The design of a non-touchscreen with physical navigation buttons makes the phone suitable for the common area and best migration practice from skype for business to Teams. Powered by Microsoft, MP52 deliver a consistent Teams calling and meeting experience and improve the productivity in daily work.

Key Features and Benefits

Excellent Calling Experience

The Yealink MP52 leverage the advantage of Yealink Optima HD voice and Noise Proof Technology. The full-duplex hands-free speakerphone with

AEC & HAC

handset makes the phone own a high performance with crystal-clear sounds, also keeps the process of each calling stably and smoothly.

Common Area Phone

That adopt to using in the common area, such as school/hospital/business scenarios, the Yealink MP52 is invulnerable to damage caused by the design of non-touchscreen and physical buttons. Moreover, the appearance of a reasonable panel structure and fewer buttons would be appropriate for deploying the phone in the common area. Users can connect Wi-Fi/Bluetooth dongle and compatible USB headset through the USB type-A port.

Efficient Management

Effectively, MP52 offers an auto-provisioning mechanism with phone development and configuration. Managers also are able to deploy, manage and update the MP52 phone in a variety of flexible ways, which include Microsoft TAC, Yealink, and Unify Square device management platforms.

Techninė specifikacija

Specifications	
Sandėlio grupė	Phone & Tablet > Telephone Systems [+665][-113]
Design	
Product type	IP Phone
Product colour	Grey
Handset type	Wired handset
Wall mountable	Yes
Mounting	Desk/Wall
Performance	
Operating system installed	Android
Operating system version	9
Hearing aid compatibility	Yes
Compatible products	Microsoft Teams
Phone features	
Caller ID	Yes
Hot desking	Yes
Common area phone (CAP)	Yes
Call waiting	Yes
Call hold	Yes
Call forwarding	Yes
Conference call	Yes
Call pick up	Yes
Full duplex	Yes
Call transfer	Yes
Call history	Yes

Emergency call	Yes
Management features	
Integrated voicemail	Yes
Display	
Touchscreen	No
Display diagonal	6.1 cm (2.4")
Display resolution	320 x 240 pixels
Backlight display	Yes
Graphical user interface (GUI) language	Multi
Audio	
Speakerphone	Yes
Microphone mute	Yes
Voice codecs	AGC, AJB, CNG, G.711alaw, G.711ulaw, G.722, G.722.1, G.722.1C, G.723, G.726, G.729A, G.729B, OPUS, PLC, Silk, VAD, iLBC
Noise reduction	Yes
Video	
Video codecs	SILK Opus, G.722, G.722.1, G.722.1C, G.711 (A/μ), G.723, G.726, G.729AB, ILBC
Network	
Ethernet LAN	Yes
Wi-Fi	No
Bluetooth	No
Ethernet LAN interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Supported network protocols	IPv4/IPv6, SNMP
DHCP client	Yes
Security algorithms	AES, HTTPS, TLS
Networking standards	IEEE 802.1x, IEEE 802.3af
Ports & interfaces	
USB 2.0 ports quantity	1
Ethernet LAN (RJ-45) ports	2
RJ-9 ports quantity	2
DC-in jack	Yes
Cable lock slot	Yes
Certificates	

Certification	CE, FCC, RoHS, ISO 9001, CCC, REACH
Power	
Power over Ethernet (PoE)	Yes
AC adapter input voltage	100 - 240 V
AC adapter output voltage	5 V
AC adapter output current	2 A
USB output current	0.5 A
Power consumption (typical)	4.5 W
Power consumption (Power over Ethernet (PoE))	6 W
Operational conditions	
Operating temperature (T-T)	10 - 95 °C
Operating relative humidity (H-H)	-10 - 50%
Weight & dimensions	
Width	212 mm
Depth	186 mm
Height	146 mm
Package width	210 mm
Package depth	238 mm
Package height	103 mm
Packaging content	
Number of handles included	1 pc(s)
Quick start guide	Yes
Cables included	LAN (RJ-45)
Stand included	Yes
Logistics data	
Products per master (outer) case	10 pc(s)
Master (outer) case gross weight	11.6 kg
Master (outer) case length	443 mm
Master (outer) case width	535 mm
Master (outer) case height	250 mm
Master (outer) case net weight	10.7 kg
Harmonized System (HS) code	85171800