



# NET SWITCH MODULE SFP 1000B- BX/SM321B TP- LINK



Modelis: SM321B

Gamintojas: TP-LINK

EAN: 6935364030520

Prekės kodas: 68451

---

## 20.99€

---

### Spotlight:

- WDM Bi-Directional SFP Module
- Supports WDM Bi-Directional technology, using a single strand of fiber, cost saving

TP-LINK's TL-SM321B adopts the latest standard 1000Base-BX, transmission over a single strand of fiber, with one different wavelength going in each direction. You can extend the network distance up to 10Km with TP-LINK's Routers, Switches, Media Converters to provide high speed and stability.

### Features

- Supports WDM Bi-Directional technology, using a single strand of fiber
- TX: 1310nm / RX: 1550nm

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

- Internal +3.3V Power Supply
- In pairs with TL-SM321A
- Plug-and-Play
- Suitable: MC220L, TL-R4199G/4299G, TL-SG3109, TL-SL3428/3452, TL-SG2109WEB/2216WEB/2224WEB, TL-SL2210WEB/2218WEB/2428WEB/2452WEB, TL-SL1351 and the other equivalent devices

Summary: TP-Link 1000Base-BX WDM Bi-Directional SFP Module. SFP transceiver type: Fiber optic, Maximum data transfer rate: 1250 Mbit/s, Interface type: SFP. Input voltage: 3.3 V. Certification: FCC, CE. Width: 55.4 mm, Depth: 12.9 mm, Height: 12.9 mm. Package width: 81.5 mm, Package depth: 122.5 mm, Package height: 38.5 mm | Vendor Homepage: <https://www.tp-link.com/products/productDetails.asp?class=&content=fea&pmodel=TL-SM321B> | Fiber cable diameters supported (core/cladding): 9/125 | Interface type: SFP | Maximum data transfer rate: 1250 | Maximum transfer distance: 10000 | Networking standards: IEEE 802.3z | Rx wavelength (max): 1310 | SFP transceiver type: Fiber optic | Single-mode fiber (SMF) supported: Yes | Tx wavelength (max): 1550 | Plug and Play: Yes | Input voltage: 3.3 | Certification: FCC, CE | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 70 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -40 - 80 | Depth: 12.9 | Height: 12.9 | Width: 55.4 | Package depth: 122.5 | Package height: 38.5 | Package weight: 60 | Package width: 81.5 | Harmonized System (HS) code: 85369010 | Model: TP-LINK TL-SM321B V3 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.000336 | Unit Calculated Weight: 0.06

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shoppro.lt](http://www.shoppro.lt) | [info@shoppro.lt](mailto:info@shoppro.lt) | +370 693 39903