

CyberPower BR700ELCD uninterruptible power supply (UPS) Line-Interactive 0.7 kVA 420 W 8 AC outlet(s)

 Gamintojas: **CYBERPOWER** · Modelis: **BR700ELCD** · EAN: **4712856270532** · Prekės kodas: **684573**


147,90 €

Kaina su PVM

 Be PVM: **122,23 €**

Sandėlyje


Prekė internetu

 Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Line-interactive UPS Topology
- ✓ Simulated Sine Wave Output
- ✓ USB Charging Port(s)
- ✓ Phone/Fax/Modem/DSL/Network Protection
- ✓ PowerPanel Management Software
- ✓ Energy Saving Technology
- ✓ Automatic Voltage Regulation (AVR)
- ✓ Surge and Spike Protection
- ✓ LCD Status Display
- ✓ Wall Mount Installation



Aprašymas

The BRICs LCD Series UPS offers home and small office users clean and stable battery backup while the featured RJ11/RJ45 port ensures phone, fax, and modem lines are protected from surges. With Automatic Voltage Regulation (AVR) stabilizes the AC signal and maintains a safe voltage, this allows the UPS to maintain safe power levels for the connected equipment without resorting to battery power. The multifunction LCD readout provides immediate access to precise information of critical power/battery condition. For convenient mounting, these units can be installed in either a horizontal or wallmounted placement to make the most of your space.

The included PowerPanel Personal Edition management software showcases the feature rich abilities such as input/output power voltage readings, self-diagnostics, and approximate battery backup time. With the Energy-Saving Technology, the BRICs LCD Series UPS can save up to 75% of

electricity therefore save your electricity expenses.

Techninė specifikacija

Specifications	
Sandėlio grupė	USV & Stromversorgung [+611][-96]
Features	
UPS topology	Line-Interactive
Output power capacity	0.7 kVA
Output power	420 W
Waveform	Sine
Input operation voltage (min)	165 V
Input operation voltage (max)	290 V
Input frequency	50/60 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	Yes
Surge energy rating	150 J
Response time	4 ms
Heat dissipation	71 BTU/h
EMI/RFI noise filtering	Yes
Surge protection	Yes
Surge protection features	Fax, Modem, Network, Telephone
Power protection features	Short circuit
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm
Ports & interfaces	
AC outlet types	Type F
AC outlets quantity	8 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	1
USB port type	USB Type-A
Modem (RJ-11) ports	2
Ethernet LAN (RJ-45) ports	2
Battery	

Battery technology	Sealed Lead Acid (VRLA)
Battery voltage	230 V
Number of batteries supported	1
Typical backup time at full load	1.5 min
Typical backup time at half load	9 min
Battery recharge time	8 h
Replacement battery cartridge	RBP0083
Design	
Form factor	Desktop
Product colour	Black
Housing material	Plastic
Cable length	1.5 m
Display type	LED
LED indicators	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 50 °C
Operating relative humidity (H-H)	0 - 90%
Storage relative humidity (H-H)	0 - 90%
Operating altitude	0 - 3000 m
Certificates	
Compliance certificates	CE, EAC, RoHS
Weight & dimensions	
Width	166 mm
Depth	288 mm
Height	118 mm
Weight	5.3 kg
Packaging data	
Package width	158 mm
Package depth	325 mm
Package height	230 mm
Package weight	6.05 kg
Logistics data	
Harmonized System (HS) code	8504408590

Other features	
Number of phases	1
Sustainability	
Sustainability compliance	Yes
Matmenys ir svoris	
Matmenys (l × p × A)	33,00cm × 16,00cm × 2,00cm