



Switch TP-LINK 8x10Base-T 100Base-TX TL- SF1008D



Modelis: TL-SF1008D

Gamintojas: TP-LINK

EAN: 6935364020071

Prekės kodas: 68474

13.99€

What This Product Does

The TL-SF1008D Fast Ethernet Switch is designed for SOHO (Small Office/Home Office) or workgroup users. All 8 ports support auto MDI/MDIX, no need to worry about the cable type, simply plug and play. Moreover, with the innovative energy-efficient technology, the TL-SF1008D can save power consumption, making it an eco-friendly solution for your business network.

High Performance

TL-SF1008D Fast Ethernet Switch provides 8 10/100Mbps Auto-Negotiation RJ45 ports. All ports support Auto MDI/MDIX function, eliminating the need for crossover cables or Uplink ports. Featuring non-blocking switching architecture, TL-SF1008D forwards and filters packets at full wire-speed for maximum throughput. With 2K Jumbo frame, the performance of large files transfers is improved significantly. And IEEE 802.3x flow control for Full Duplex mode and backpressure for Half Duplex

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

mode alleviate the traffic congestion and make TL-SF1008D work reliably.

TP-Link Green Technology

This new generation TL-SF1008D Fast Ethernet Switch features the latest innovative energy-efficient technologies that can greatly expand your network capacity with much less power. It automatically adjusts power consumption according to the link status and cable length to limit the carbon footprint of your network.

It also complies with the EU'S RoHS, prohibiting the use of certain hazardous materials. Besides, 70% of the packaging material can be recycled.

Easy to Use

The auto features of this switch make installation plug and play and hassle-free. No configuring is required. Auto MDI/MDIX eliminates the need for crossover cables. Auto-negotiation on each port senses the link speed of a network device (10, 100 Mbps) and intelligently adjusts for compatibility and optimal performance.

- 8x 10/100Mbps auto-negotiation RJ45 ports, supports auto MDI/MDIX
- Green Ethernet technology saves power consumption
- IEEE 802.3x flow control provides reliable data transfer
- Plastic case, desktop design
- Plug and play, no configuration required

Summary: TP-Link TL-SF1008D. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100), Basic switching RJ-45 Ethernet ports quantity: 8. Full duplex. MAC address table: 1000 entries, Switching capacity: 1.6 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3x. DC input voltage: 5 V. Power connector: DC-in jack | Vendor Homepage: <https://www.tp-link.com/us/home-networking/8-port-switch/tl-sf1008d/> | Switch type: Unmanaged | Basic switching RJ-45 Ethernet ports quantity: 8 | Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100) | Fast Ethernet (copper) ports quantity: 8 | Power connector: DC-in jack | 10G support: No | Auto MDI/MDI-X: Yes | Auto-negotiation: Yes | Copper ethernet cabling technology: 100BASE-TX/10BASE-T | Flow control support: Yes | Full duplex: Yes | Half duplex: Yes | Networking standards: IEEE 802.3/IEEE 802.3ab/IEEE 802.3x | MAC address table: 1000 | Packet buffer memory: 0.768 | Store-and-forward: Yes | Switching capacity: 1.6 | Supported network protocols: CSMA/CD, TCP/IP | LED

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

indicators: Yes | Product colour: White | Rack mounting: No | Stackable: No | Fanless: Yes | AC input frequency: 50/60 | AC input voltage: 100 - 240 | DC input voltage: 5 | Input current: 0.6 | Power consumption (max): 2.05 | Power source: DC | Power supply included: No | Power over Ethernet (PoE): No | Heat dissipation: 6.99 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 95 | Storage temperature (T-T): -40 - 70 | Depth: 79 | Height: 22.5 | Width: 134.5 | User guide: Yes | AC adapter included: Yes | Package depth: 139 | Package height: 85 | Package type: Box | Package weight: 240 | Package width: 100 | Sustainability compliance: Yes | Compliance certificates: CE/Federal Communications Commission (FCC)/RoHS | Harmonized System (HS) code: 85176990 | Units per Shipping Box: 60 | Unit Calculated Volume: 0.00146 | Unit Calculated Weight: 0.263

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903