

FSP NanoFit 600 uninterruptible power supply (UPS) Standby (Offline) 0.6 kVA 360 W 6 AC outlet(s)

Gamintojas: **FSP** · Modelis: **PPF3602301** · EAN: **4713224521119** · Prekės kodas: **684764**



98,91 €

Kaina su PVM

Be PVM: **81,74 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Compact size can be desktop or wall-mounted
- ✓ Excellent microprocessor control guarantees high reliability
- ✓ Auto restart while AC is recovering
- ✓ Simulated sine wave
- ✓ Cold start function
- ✓ 6 outlets
- ✓ 2 ports USB charger 5V / 1A (Max.)



Aprašymas

A compact size with stand and mounting flexibility Off line UPS to provide the expected backup power for home, gaming or personal appliances.

Compact size can be desktop or wall-mounted

RJ45 Surge Protection safeguards your equipment against damaging surges and spikes that travel along utility and internet lines.

Nanofit 600/800 can be monitored by computer software
(This function only available for UPS with Type-B com. Port)

FSP UPS provides back up battery power so you can work through short and medium length power outages.

Protect your productivity from the constant threat of bad power and lost data.

Techninė specifikacija

Specifications	
Sandėlio grupė	USV & Stromversorgung [+611][-96]
Features	
UPS topology	Standby (Offline)
Output power capacity	0.6 kVA
Output power	360 W
Waveform	Sine
Input operation voltage (min)	220 V
Input operation voltage (max)	240 V
Input frequency	50/60 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Output frequency regulation	±1 Hz
Output voltage regulation	±10%%
Response time	6 ms
Noise level	40 dB
Power protection features	Overcharge, Overdischarge, Overload
Ports & interfaces	
AC outlet types	Type F
AC outlets quantity	6 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	2
USB port type	USB Type-A
Ethernet LAN (RJ-45) ports	2
Battery	
Battery capacity	4.5 Ah
Battery voltage	12 V
Number of batteries supported	1
Typical backup time at full load	13 min

Battery recharge time	8 h
-----------------------	-----

Cold start	Yes
------------	-----

Design

Form factor	Compact
-------------	---------

Product colour	Black
----------------	-------

Display type	LCD
--------------	-----

Operational conditions

Operating temperature (T-T)	0 - 40 °C
-----------------------------	-----------

Operating relative humidity (H-H)	0 - 90%
-----------------------------------	---------

Safety regulation & standards

Safety	CE
--------	----

Weight & dimensions

Width	158.5 mm
-------	----------

Depth	305 mm
-------	--------

Height	95 mm
--------	-------

Weight	2.6 kg
--------	--------

Logistics data

Harmonized System (HS) code	85078000
-----------------------------	----------

Matmenys ir svoris

Svoris	3,02kg
--------	--------