FSP Clippers RT 2K uninterruptible power supply (UPS) Double-conversion (Online) 2 kVA 2000 W

Gamintojas: **FSP** · Modelis: **PPF20A0400** · EAN: **4713224524899** · Prekės kodas: **684767**

691,90 €

Kaina su PVM

Be PVM: **571,82 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ True double conversion
- ✓ Output power factor 1
- ✓ Super Charger up to 8A
- ✓ Output voltage regulation < 1%
- ✓ Higher output crest ratio 3:1
- ✓ 50Hz/60Hz frequency converter mode
- ✓ Programmable power management outlets
- ✓ Emergency power off function (EPO)
- ✓ Hot-swappable battery design
- ✓ ECO mode for energy saving



Aprašymas

FSP Clippers RT Series Clippers series is a premium featured online double conversion UPS with Rack/Tower design and high efficiency to reduce customer's total cost of ownership. The internal hot-swappable battery increases system reliability and reduces MTTR; the parallel function is designed for future equipment expansion. Its special firmware design can adapt to various applications like laser printers and ultrasound devices and supports long backup time with battery monitoring.

Techninė specifikacija

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Specifications	
Sandėlio grupė	USV & Stromversorgung [+611][-96]
Features	
UPS topology	Double-conversion (Online)
Output power capacity	2 kVA
Output power	2000 W
Waveform	Sine
Input operation voltage (min)	110 V
Input operation voltage (max)	300 V
Input frequency	40/70 Hz
Output operation voltage (min)	208 V
Output operation voltage (max)	240 V
Output frequency	46/64 Hz
Output voltage regulation	1%
Response time	4 ms
Number of input phases	1
Power factor	0.99
Crest factor	3:1
ECO mode	Yes
Total Harmonic Distortion (THD) (linear load)	2%
Total Harmonic Distortion (THD) (non-linear load)	4%
Noise level	50 dB
Surge protection	Yes
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Fault, Overload alarm, Low battery alarm
Ports & interfaces	
AC outlet types	C13 coupler
USB port	Yes
USB 2.0 ports quantity	1
USB port type	USB Type-B
Serial interface	Yes
Serial interface type	RS-232
Emergency Power Off (EPO) connector	Yes
Battery	

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Battery capacity	9 Ah
Battery voltage	12 V
Number of battery cells	4
Typical backup time at full load	33 min
Battery recharge time	3 h
Hot-swap battery	Yes
Design	
Form factor	Rackmount/Tower
Product colour	Black
Cooling type	Active
Built-in fan	Yes
Control type	Buttons
Display type	LCD
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 90%
Certificates	
Compliance certificates	CE
Certification	EMC EN62040-2 C2
Weight & dimensions	
Width	438 mm
Depth	510 mm
Height	88 mm
Weight	19.5 kg
Logistics data	
Harmonized System (HS) code	85078000
Other features	
Packaging content	UPS, user manual, software CD, C14-C13 cable, USB cable, tower stands, mounting ears & screws
Sustainability	
Sustainability compliance	Yes
Matmenys ir svoris	
Svoris	23,20kg

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903