FSP FP 2000 uninterruptible power supply (UPS) Line-Interactive 2 kVA 1200 W 4 AC outlet(s)

Gamintojas: **FSP** · Modelis: **PPF12A0800** · EAN: **4711140487663** · Prekės kodas: **684770**

215,90 €

Kaina su PVM

Be PVM: **178,43 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Compact size
- ✓ Excellent microprocessor control for high reliability
- ✓ Boost and buck AVR for voltage stabilization
- ✓ Auto restart while AC is recovering
- ✓ Simulated sine wave
- ✓ Off-mode charging
- ✓ Cold start function

Aprašymas

The line-interactive FP Series UPS with a compact size can provide stable power protection against surges and spikes. It is ideal for PC users or small business companies, as well as for small telecom applications.
Its embedded microprocessor controller guarantees high reliability
It can automatically restart while AC power is recovering. With a Simulated sine wave, off-mode charging, and cold start function, it will be a good choice.

Techninė specifikacija

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Specifications	
Sandėlio grupė	USV & Stromversorgung [+611][-96]
Features	
UPS topology	Line-Interactive
Output power capacity	2 kVA
Output power	1200 W
Waveform	Sine
Input operation voltage (min)	162 V
Input operation voltage (max)	290 V
Input frequency	50/60 Hz
Output operation voltage (min)	100 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Output voltage regulation	10%
Automatic Voltage Regulation (AVR)	Yes
Response time	6 ms
Noise level	40 dB
Power protection features	Battery discharge, Overcharge, Overload
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm
Auto-restart	Yes
Ports & interfaces	
AC outlet types	Type F
AC outlets quantity	4 AC outlet(s)
Battery	
Battery capacity	9 Ah
Battery voltage	12 V
Number of batteries supported	2
Battery recharge time	6 h
Battery recharge time(90%)	6 h
Automatic battery test	Yes
Cold start	Yes
Off-mode charging	Yes
Design	

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Form factor	Mini Tower
Product colour	Black
LED indicators	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	0 - 90%
Certificates	
Compliance certificates	CE, EAC
Packaging content	
Batteries included	Yes
Manual	Yes
Weight & dimensions	
Width	130 mm
Depth	320 mm
Height	182 mm
Weight	11 kg
Packaging data	
Package width	190 mm
Package depth	390 mm
Package height	275 mm
Package type	Box
Logistics data	
Harmonized System (HS) code	85078000
Other features	
Packaging content	UPS & user manual
Sustainability	
Sustainability compliance	Yes
Matmenys ir svoris	
Matmenys (I × P × A)	40,00cm × 19,00cm × 27,00cm
Svoris	11,43kg

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903