

# FSP ST 1500 uninterruptible power supply (UPS) Line-Interactive 1.5 kVA 900 W

Gamintojas: **FSP** · Modelis: **PPF9004000** · EAN: **4713224528965** · Prekės kodas: **684779**



## 229,90 €

Kaina su PVM

Be PVM: **190,00 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ Simulated sine wave
- ✓ Built-in AVR for voltage stabilization
- ✓ Easy replacement battery compartment & hot-swappable battery design
- ✓ Built-in USB communication port and RJ-45 network protection
- ✓ Off-mode charging
- ✓ Cold start function
- ✓ Auto restart while AC is recovering



## Aprašymas

### ST Series intelligent UPS

A Great Partner for Small Equipment

The ST series is equipped with automatic voltage regulation to reduce the impact of unstable voltage on equipment. The intelligent UPS' functions can also provide power during outages, and the battery automatically charges when power is restored. FSP's intelligent UPS can provide equipment with an uninterrupted supply of power at any time.

## Techninė specifikacija

**Specifications**

|                |                                   |
|----------------|-----------------------------------|
| Sandėlio grupė | USV & Stromversorgung [+611][-96] |
|----------------|-----------------------------------|

**Features**

|                                |                                                                 |
|--------------------------------|-----------------------------------------------------------------|
| UPS topology                   | Line-Interactive                                                |
| Output power capacity          | 1.5 kVA                                                         |
| Output power                   | 900 W                                                           |
| Waveform                       | Sine                                                            |
| Input operation voltage (min)  | 81 V                                                            |
| Input operation voltage (max)  | 270 V                                                           |
| Input frequency                | 50/60 Hz                                                        |
| Output operation voltage (min) | 110 V                                                           |
| Output operation voltage (max) | 240 V                                                           |
| Output frequency               | 50/60 Hz                                                        |
| Output voltage regulation      | 5%                                                              |
| Power protection features      | Battery discharge, Overcharge, Overload                         |
| Audible alarm(s)               | Yes                                                             |
| Audible alarm modes            | Alarm when on battery, Fault, Low battery alarm, Overload alarm |
| Power source type              | AC                                                              |

**Ports & interfaces**

|                              |            |
|------------------------------|------------|
| Number of output IEC jumpers | 8          |
| USB port                     | Yes        |
| USB 2.0 ports quantity       | 1          |
| USB port type                | USB Type-B |
| Ethernet LAN (RJ-45) ports   | 2          |

**Battery**

|                         |       |
|-------------------------|-------|
| Battery capacity        | 18 Ah |
| Battery voltage         | 12 V  |
| Number of battery cells | 2     |
| Battery recharge time   | 6.8 h |
| Hot-swap battery        | Yes   |

**Design**

|                |        |
|----------------|--------|
| Form factor    | Tower  |
| Product colour | Black  |
| Cooling type   | Active |

|                                   |           |
|-----------------------------------|-----------|
| Built-in fan                      | Yes       |
| Control type                      | Buttons   |
| Display type                      | LCD       |
| Operational conditions            |           |
| Operating temperature (T-T)       | 0 - 40 °C |
| Operating relative humidity (H-H) | 0 - 90%   |
| Packaging content                 |           |
| Batteries included                | Yes       |
| Weight & dimensions               |           |
| Width                             | 99 mm     |
| Depth                             | 410 mm    |
| Height                            | 280 mm    |
| Weight                            | 12 kg     |
| Matmenys ir svoris                |           |
| Svoris                            | 13,00kg   |