

ATEN 1-Local/Remote Share Access Single Port DVI KVM over IP Switch

Gamintojas: **ATEN** · Modelis: **CN9600** · EAN: **4719264649271** · Prekės kodas: **684895**



1 240,90 €

Kaina su PVM

Be PVM: **1 025,54 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Compact and slim design for space utility optimization
- ✓ Provides a FPGA graphics processor for better image quality and enhanced fps (frames per second) throughput for crisp video display response
- ✓ Provides over-IP capability to DVI KVM switches that do not have built-in over-IP functionality*
- ✓ Local console provides USB keyboard and mouse support
- ✓ A mini USB port on the front panel serves as a Laptop USB Console (LUC) port
- ✓ Two 10/100/1000 Mbps NICs for redundant LAN or two IP operation
- ✓ Dual Power Supply for power backup
- ✓ Supports multiplatform server environments: Windows, Mac, Sun, Linux and VT100 based serial devices
- ✓ Virtual Media support**
- ✓ High video resolution – up to 1920 x 1200 @ 60Hz for both local and remote consoles



Aprašymas

The CN9600 DVI KVM over IP Switch is a cost-efficient over-IP device, which allows remote access of digital video, audio and virtual media via remote control of a PC or workstation. The CN9600 enables over-IP capability by connecting compatible ATEN DVI KVM switch and/or LCD console, such as the CS1768 (8-Port USB DVI/Audio KVM Switch) or the CL3800 (DVI LCD Console).

- 1x CN9600 DVI KVM over IP Switch
- 1x KVM Cable (DVI-D, USB, Audio; 1.8 m/6 ft)
- 1x USB Cable (1.8 m/6 ft)
- 1x Power Adapter
- 1x Mounting Kit
- 1x User Instructions

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Switches [+2183][-1086]
Ports & interfaces	
Keyboard port type	USB
Mouse port type	USB
Video port type	DVI-D
Console ports	3.5mm headphone, DVI-D, USB A
DVI-D ports quantity	2
USB 2.0 Type-B ports quantity	1
Console USB ports quantity	2
USB connector type	Mini-USB B, USB Type-A
PS/2 ports quantity	1
Serial port type	RJ-45
Serial ports quantity	2
Audio connections	Yes
Headphone outputs	1
Number of microphone inputs	1
DC-in jack	Yes
Network	
Ethernet LAN	Yes
Ethernet LAN (RJ-45) ports	2
Performance	
Maximum resolution	1920 x 1200 pixels
Video bandwidth	60 Hz
Firmware upgradeable	Yes
Design	
Product colour	Black
Housing material	Metal

LED indicators	Yes
Display	
Built-in display	No
Power	
Power source	DC
Input voltage	5 V
Power consumption (typical)	5.55 W
Sustainability	
Compliance certificates	RoHS
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Weight & dimensions	
Width	154.9 mm
Depth	200 mm
Height	28.5 mm
Weight	1.24 kg
Packaging data	
Package width	98 mm
Package depth	325 mm
Package height	210 mm
Package weight	1.61 kg
Logistics data	
Master (outer) case net weight	6.2 kg
Harmonized System (HS) code	85176200
Master (outer) case width	342 mm
Master (outer) case length	512 mm
Master (outer) case height	232 mm
Master (outer) case gross weight	8.72 kg
Products per master (outer) case	5 pc(s)