

Dahua Technology DHI-NVR5216-16P-EI network video recorder

Gamintojas: **DAHUA TECHNOLOGY** · Modelis: **DHI-NVR5216-16P-EI** · EAN: **6923172589828** · Prekės kodas: **685110**



936,90 €

Kaina su PVM

Be PVM: **774,30 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats
- ✓ Max. decoding capability: 32 × 1080p@30 fps or 16 × 4MP@30 fps
- ✓ Max. 384/384/384 Mbps incoming/recording/outgoing bandwidth
- ✓ Supports IP cameras with a resolution up to 32 MP
- ✓ Supports AcuPick with up to 16 channels
- ✓ Supports N+M cluster, iSCSI
- ✓ AI by Recorder supports 2-channel face detection and recognition, up to 20 face databases and 20,000 face images; 4-channel perimeter protection; 8-channel SMD Plus
- ✓ AI by Camera supports face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting
- ✓ Supports EPTZ, and one-click arming and disarming



Techninė specifikacija

Specifications

Sandėlio grupė

Entertainment Electronics > Multimedia [+192][-84]

Performance

Video input channels

16 channels

Maximum resolution	3840 x 2160 pixels
Alarm input channels	4
Alarm output channels	2
Audio formats supported	G.711u, PCM
Video formats supported	H.264, H.264+, H.265, H.265+
Image formats supported	MJPEG
Face detection	Yes

Hard drive

Number of HDDs installed	2
--------------------------	---

Ports & interfaces

Ethernet LAN (RJ-45) ports	1
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) ports quantity	16
HDMI ports quantity	1
VGA (D-Sub) output ports	1
USB 2.0 ports quantity	1
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
RS-485 ports	1
RS-232 interface	Yes
Supported network protocols	HTTP; HTTPS; TCP/IP; IPv4; UDP; NTP; DHCP; DNS; SMTP; UPnP; DDNS; Alarm Server; IP Search (Supports Dahua IP camera, DVR, NVS, etc.); Multicast; P2P; Auto Registration; iSCSI

Power

AC input voltage	100 - 240 V
AC input frequency	47 - 63 Hz

Operational conditions

Operating temperature (T-T)	-10 - 55 °C
Operating relative humidity (H-H)	10 - 39%
Storage temperature (T-T)	-20 - 60 °C

Technical details

Compliance certificates	Federal Communications Commission (FCC)
-------------------------	---

Weight & dimensions

Width	375 mm
Depth	329.3 mm
Height	53 mm

Weight	2.66 kg
Package width	451 mm
Package depth	147 mm
Package height	425 mm
Package weight	3.82 kg