

CyberPower BR1200ELCD uninterruptible power supply (UPS) Line-Interactive 1.2 kVA 720 W 8 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **BR1200ELCD** · EAN: **4712856270549** · Prekės kodas: **685117**



219,91 €

Kaina su PVM

Be PVM: **181,74 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Line-interactive UPS Topology
- ✓ Simulated Sine Wave Output
- ✓ USB Charging Port(s)
- ✓ Phone/Fax/Modem/DSL/Network Protection
- ✓ PowerPanel Management Software
- ✓ Energy Saving Technology
- ✓ Automatic Voltage Regulation (AVR)
- ✓ Surge and Spike Protection
- ✓ LCD Status Display
- ✓ Wall Mount Installation



Aprašymas

The BRICs LCD Series UPS with LCD can supply clean and stable power to protect your equipment. The include PowerPanel Personal Edition management software showcases the feature rich abilities of this UPS such as input /output power voltage readings, self-diagnostics, scheduled shutdown, and approximate battery back-up time reading. These UPS units can be placed in either a horizontal or wallmount position to mark the most of your space. With Energy-Saving Technology, BRICs LCD Series UPS can save upto 75% of electricity and save your electricity bill. You can easy charge AA/AAA battery Via USB charge with battery charger.

Techninė specifikacija

Specifications

Sandėlio grupė	USV & Stromversorgung [+611][-96]
----------------	-----------------------------------

Features

UPS topology	Line-Interactive
Output power capacity	1.2 kVA
Output power	720 W
Waveform	Sine
Input operation voltage (min)	165 V
Input operation voltage (max)	290 V
Input frequency	50/60 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	Yes
Surge energy rating	150 J
Response time	4 ms
Heat dissipation	137 BTU/h
EMI/RFI noise filtering	Yes
Surge protection	Yes
Surge protection features	Fax, Modem, Network, Telephone
Power protection features	Short circuit
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm

Ports & interfaces

AC outlet types	Type F
AC outlets quantity	8 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	1
USB port type	USB Type-A
Modem (RJ-11) ports	2
Ethernet LAN (RJ-45) ports	2

Battery

Battery technology	Sealed Lead Acid (VRLA)
Battery voltage	230 V

Number of batteries supported	2
Typical backup time at full load	2 min
Typical backup time at half load	9 min
Battery recharge time	8 h
Replacement battery cartridge	RBP0063
Design	
Form factor	Desktop
Product colour	Black
Housing material	Plastic
Cable length	1.5 m
Display type	LCD
LED indicators	Battery level, Power, Status
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 50 °C
Operating relative humidity (H-H)	0 - 90%
Storage relative humidity (H-H)	0 - 90%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 3000 m
Certificates	
Compliance certificates	CE, EAC, RoHS
Weight & dimensions	
Width	166 mm
Depth	288 mm
Height	118 mm
Weight	8.2 kg
Packaging data	
Package width	158 mm
Package depth	325 mm
Package height	230 mm
Package weight	8.43 kg
Logistics data	
Harmonized System (HS) code	8504408590
Other features	

Number of phases	1
------------------	---

Sustainability

Sustainability compliance	Yes
---------------------------	-----

Matmenys ir svoris

Matmenys (I × P × A)	33,00cm × 16,00cm × 23,00cm
----------------------	-----------------------------

Svoris	8,36kg
--------	--------