

CyberPower BR1000ELCD uninterruptible power supply (UPS) Line-Interactive 1 kVA 600 W 8 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **BR1000ELCD** · EAN: **4712856271157** · Prekės kodas: **685133**



169,90 €

Kaina su PVM

Be PVM: **140,41 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Line-interactive UPS Topology
- ✓ Simulated Sine Wave Output
- ✓ USB Charging Port(s)
- ✓ Phone/Fax/Modem/DSL/Network Protection
- ✓ PowerPanel Management Software
- ✓ Energy Saving Technology
- ✓ Automatic Voltage Regulation (AVR)
- ✓ Surge and Spike Protection
- ✓ LCD Status Display
- ✓ Wall Mount Installation



Aprašymas

CyberPower BR1000ELCD offers home and office users a reliable battery backup and safeguards office PCs, network communication equipment, and other electronic devices from surges, spikes, brownouts and other power incidents. Designed with GreenPower UPS™ Technology to improve UPS operating efficiency and to minimize its energy consumption, users can enjoy significant energy cost savings over conventional UPS systems.

The UPS provides Automatic Voltage Regulation (AVR) to maintain a safe voltage for connected equipment. The featured data line protection protects phones, networks, and other communication equipment against surges/spikes and other power irregularities. Users can access precise information of critical power/battery conditions with the LCD status monitor.

Techninė specifikacija

Specifications	
Sandėlio grupė	USV & Stromversorgung [+611][-96]
Features	
UPS topology	Line-Interactive
Output power capacity	1 kVA
Output power	600 W
Waveform	Sine
Input operation voltage (min)	167 V
Input operation voltage (max)	295 V
Input frequency	45/65 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Maximum current	4.46 A
Surge energy rating	150 J
Response time	4 ms
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm
Ports & interfaces	
AC outlet types	Type F
Power plug	Type F
AC outlets quantity	8 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	2
USB port type	USB Type A/USB Type-C
Ethernet LAN (RJ-45) ports	2
Battery	
Battery technology	Sealed Lead Acid (VRLA)
Typical backup time at full load	1 min
Typical backup time at half load	5 min
Battery recharge time	8 h
Hot-swap battery	Yes
Design	
Form factor	Desktop

Product colour	Black
Control type	Buttons
Display type	LCD
LED indicators	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 50 °C
Operating relative humidity (H-H)	0 - 90%
Storage relative humidity (H-H)	0 - 90%
Operating altitude	0 - 3000 m
Certificates	
Compliance certificates	CE, RoHS
Packaging content	
Cables included	Serial, USB cable
Manual	Yes
Weight & dimensions	
Width	288 mm
Depth	166 mm
Height	118 mm
Weight	6.5 kg
Packaging data	
Package width	158 mm
Package depth	325 mm
Package height	230 mm
Package weight	6.95 kg
Logistics data	
Harmonized System (HS) code	8504408590
Country of origin	China
Sustainability	
Sustainability compliance	Yes
Matmenys ir svoris	
Matmenys (I × P × A)	33,00cm × 16,00cm × 23,00cm
Svoris	6,90kg