D-Link DGS-1005P/E network switch Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Gamintojas: **D-LINK** · Modelis: **DGS-1005P/E** · EAN: **790069440984** · Prekės kodas: **68548**



49.90€ ~~68.90€~~

Kaina su PVM

Be PVM: **41.24€**

In Stock

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Unmanaged
- ✓ Quality of Service (QoS) support
- ✓ Basic switching RJ-45 Ethernet ports quantity: 5
- ✓ 10BASE-T, 100BASE-TX, 1000BASE-T
- ✓ MAC address table: 2000 entries Switching capacity: 10 Gbit/s
- ✓ Power supply included Power over Ethernet (PoE)





Aprašymas

Fast. Compact. Convenient.

The D-Link DGS-1005P 5-Port Desktop Gigabit PoE+ Switch enables you to connect Power over Ethernet (PoE) devices such as wireless access points (APs), network video cameras and IP phones to the network. Built with home and small business users in mind, the DGS-1005P is compact and operates silently, making it ideal for most rooms and offices.

Gigabit Performance.

The DGS-1005P features plug-and-play installation and requires no configuration.

Automatic MDI/MDI-X support on all ports removes the need for crossover cables when connecting to another switch, and auto-negotiation on each port intelligently adjusts the port speed for compatibility with the connected device. With wire-speed filtering and store-and-forward switching, the DGS-1005P maximises network performance while minimising the transmission of bad network packets.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Power Over Ethernet+

The DGS-1005P features four Gigabit Ethernet ports that support the IEEE 802.3af and IEEE 802.3at PoE, supplying up to 30 W on each PoE port and providing a total power budget of 60 W.

You can connect compatible devices to the DGS-1005P without using an additional power supply. This allows you to save on cabling and power supplies and to install devices on locations without immediate access to power outlets.

Green Technology

The DGS-1005P features green technology such as IEEE 802.3az Energy-Efficient Ethernet (EEE), link status detection, and cable length detection.

EEE adjusts the power consumption of the switch based on network utilisation, reducing energy use during periods of inactivity. Link status detection powers down unused ports, saving power when connected devices are shut down or disconnected. Cable length detection adjusts the power output of the port based on the cable length, reducing the power requirements of the switch.

Compact and Silent

The compact design of the DGS-1005P allows placement in most locations, including those where space is at a premium.

The desktop form factor provides everything you need to set up a new network or expand an existing network, while the fanless design ensures silent operation even in noise-sensitive areas such as workstations and meeting rooms.

Techninė specifikacija

Management features	
Switch type	Unmanaged
Quality of Service (QoS) support	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	5
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Gigabit Ethernet (copper) ports quantity	5
Power connector	DC-in jack
Network	
Networking standards	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Full duplex	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
MAC address auto-learning supported	Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Data transmission	
MAC address table	2000 entries
Switching capacity	10 Gbit/s
Forwarding rate	7.44 Mpps
Store-and-forward	Yes
Security	
Packet filtering	7.44 Mpps
Design	
Rack mounting	No
Product colour	Black
Housing material	Metal
LED indicators	Activity, Link, PoE, Power, Speed, Status
Wall mountable	Yes
Performance	
Buffer size	64 KB
Plug and Play	Yes
Power	
Power supply included	Yes
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) ports quantity	4
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	60 W
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-10 - 70 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Weight & dimensions	
Width	100 mm
Depth	98 mm
Height	28 mm
Weight	260 g
Certificates	

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Certification	CE, BSMI, FCC , VCCI, RCM, cUL, CB, LVD, BSMI
Matmenys ir svoris	
Matmenys (I × P × A)	25.00cm × 7.00cm × 20.00cm
Svoris	1.06kg

Dokumentai ir vaizdo įrašai

- Quick start guide
- Product leaflet

Gamintojo ir saugos informacija

MANUFACTURER

D-Link

EU RESPONSIBLE PERSON

D-Link Benelux
Postbus 48, 5480 AA Schijndel, NL
dlink.com

DISTRIBUTOR

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt