

CyberPower PR1000ERT2UC uninterruptible power supply (UPS) Line-Interactive 1 kVA 1000 W 10 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **PR1000ERT2UC** · EAN: **4711027798868** · Prekės kodas: **686176**



753,90 €

Kaina su PVM

Be PVM: **623,06 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Line-interactive UPS Topology
- ✓ Active PFC Compatible
- ✓ Toolless Battery Replacement
- ✓ High Output Power Factor
- ✓ Overload Protection
- ✓ Quick Charging Technology
- ✓ Surge and Spike Protection
- ✓ LCD Status Display
- ✓ Serial Connectivity Port
- ✓ PowerPanel Management Software



Aprašymas

CyberPower PR1000ERT2UC with rackmount design guarantees power backup protection for home theater systems, multimedia devices, IT equipment, computers, workstations, NAS/Storage devices, telecom devices, networking devices, and surveillance systems. The UPS adopts line-interactive topology with Automatic Voltage Regulation (AVR) function, and offers stabilized Pure Sine Wave output to ensure high power quality.

The UPS's output power factor is 1, which means it is capable of connecting to more critical loads than conventional UPS. It also features Battery Management Technology to help batteries obtain optimal life span by balancing battery string voltage. Two-phase battery charging can charge the battery quickly and safely. The hot-swappable battery packs allow for easy maintenance without power interruption. Its multi-functional matrix LCD supports intuitive operation and quick configuration. The LCD panel is also rotatable to meet installation requirements.

Techninė specifikacija

Specifications	
Sandėlio grupė	USV & Stromversorgung [+611][-96]
Features	
UPS topology	Line-Interactive
Output power capacity	1 kVA
Output power	1000 W
Waveform	Pure sine
Input operation voltage (min)	200 V
Input operation voltage (max)	240 V
Input frequency	50/60 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	Yes
Maximum current	16 A
Surge energy rating	2430 J
Response time	6 ms
Heat dissipation	96.7 BTU/h
Number of input phases	1
Number of output phases	1
Output power factor	1
Power Factor Correction (PFC) type	Active
Emergency Power Off (EPO)	Yes
EMI/RFI noise filtering	Yes
Surge protection	Yes
Power protection features	Overload

Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm
Power source type	AC
Detachable power cord	Yes
Ports & interfaces	
AC outlet types	C13 coupler
Power plug	C14 coupler
AC outlets quantity	10 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	1
USB port type	USB Type-B
Serial interface	Yes
Serial interface type	RS-232
Serial ports quantity	2
RS-232 ports	2
Ethernet LAN (RJ-45) ports	2
Emergency Power Off (EPO) connector	Yes
Battery	
Battery technology	Sealed Lead Acid (VRLA)
Number of batteries supported	1
Typical backup time at full load	6.5 min
Typical backup time at half load	19.3 min
Battery recharge time	3 h
Hot-swap battery	Yes
Design	
Form factor	Rackmount/Tower
Product colour	Black
Housing material	Metal
Rack capacity	2U
Extended battery module rack capacity	2U
Cable length	3.05 m
Cooling type	Active
Built-in fan	Yes
Control type	Buttons
Display type	LCD
LED indicators	Yes

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Certificates

Compliance certificates	CE, Federal Communications Commission (FCC), RCM, RoHS, UL, VCCI
-------------------------	--

Packaging content

Batteries included	Yes
Rack mount kit	Yes
Cables included	Serial
Manual	Yes

Weight & dimensions

Width	433 mm
Depth	500 mm
Height	86.5 mm
Weight	32 kg

Packaging data

Package width	560 mm
Package depth	620 mm
Package height	275 mm
Package weight	38.8 kg
Package type	Box

Logistics data

Country of origin	China
-------------------	-------

Other features

Battery type	RBP0128
--------------	---------

Sustainability

Sustainability compliance	Yes
---------------------------	-----