

TP-Link TL-SF1006P network switch Unmanaged Fast Ethernet (10/100) Power over Ethernet (PoE) Black

Gamintojas: **TP-LINK** · Modelis: **TL-SF1006P** · EAN: **6935364030933** · Prekės kodas: **68627**



45,90 €

Kaina su PVM

Be PVM: **37,93 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 6x 10/100 Mbps RJ45 ports
- ✓ 4x PoE+ ports transfer data and power on individual cables
- ✓ Works with IEEE 802.3af/at compliant PDs
- ✓ Up to 250m data and power transmitting range under Extend Mode**
- ✓ Priority Mode ensures high priority of ports 1-2 to guarantee the quality of sensitive application
- ✓ Supports PoE Power up to 30 W for each PoE port
- ✓ Supports PoE Power up to 67 W for all PoE ports*
- ✓ Plug and play with no configuration required



Aprašymas

Professional High-Power Switch with 4 PoE+ Ports

Plug and Play, with PoE Transmission for Surveillance up to 250 m

Dedicated 4-Poart PoE+ Switch (67 W Budget) for Numerous Applications

Compliance with the 802.3af/at PoE standard supports up to 15.4 W on each PoE port. The total 41 W PoE power budget* for the 4x PoE ports opens up a wide range of applications, such as surveillance for offices, dormitories, and small businesses. It is fully compatible with IP cameras, access points, IP phones, computers, printers, and more.

Ideal for IP Surveillance—Up to 250 m Transmissions

With extend mode, the PoE transmission distance reaches up to 250 m**—perfect for IP Camera deployment in large areas.

**The speed of the ports in extend mode will downgrade to 10 Mbps. The actual transmission distance may vary due to power consumption of PoE-powered devices or the cable quality and type.

Priority Video Quality Guaranteed

Quality of sensitive applications like video monitoring in critical business areas is guaranteed by offering higher priority options for ports 1-2 when one-touch Priority Mode is on.

Intelligent Power Management

When total power consumption exceeds 67 W, the intelligent power management will cut the lower priority port power. This ensures the high priority port's power supply and protects the device from power overload. It also automatically detects and provides the required power for your PoE devices while protecting your PoE and non-PoE equipment from being damaged.

Durable Metal Casing

The interior components of TL-SF1006P are protected by high-quality metal casing to ensure a long product life. Having passed an array of stringent reliability tests, TL-SF1006P delivers switching performance you can depend on.

Techninė specifikacija

Specifications	
Sandėlio grupė	Networking and Security > Switches [+0][-2]
Management features	
Switch type	Unmanaged
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	6
Basic switching RJ-45 Ethernet ports type	Fast Ethernet (10/100)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Network	
Networking standards	IEEE 802.3af, IEEE 802.3at
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 100BASE-T
Cable types supported	Cat3, Cat4, Cat5, Cat5e
Full duplex	Yes
Half duplex	Yes
Flow control support	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
MAC address auto-learning supported	Yes
MAC address auto-aging supported	Yes

Data transmission

MAC address table	2000 entries
Switching capacity	1.2 Gbit/s
Forwarding rate	0.8928 Mpps
Store-and-forward	Yes
Jumbo frames support	Yes
Jumbo frames	2000

Design

Rack mounting	No
Stackable	No
Product colour	Black
Housing material	Metal
LED indicators	Yes

Performance

Fanless	Yes
---------	-----

Power

Power source	DC/PoE
Power supply included	Yes
AC input voltage	220 V
AC input frequency	50 Hz
DC input voltage	53.5 V
Input current	1.31 A
Power consumption (max)	74 W

Power over Ethernet (PoE)

Power over Ethernet (PoE)	Yes
Power over Ethernet plus (PoE+) ports quantity	4
Total Power over Ethernet (PoE) budget	67 W

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Heat dissipation	252.34 BTU/h

Weight & dimensions

Width	158 mm
Depth	101 mm
Height	25 mm
Packaging content	
User guide	Yes
Packaging data	
AC adapter included	Yes
Package type	Box
Package width	131 mm
Package depth	196 mm
Package height	121 mm
Package weight	870 g
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
Certification	FCC, CE, RoHS
Logistics data	
Harmonized System (HS) code	85176990
Sustainability	
Sustainability compliance	Yes
Matmenys ir svoris	
Matmenys (I × P × A)	20,00cm × 12,00cm × 13,00cm
Svoris	0,87kg