

InLine 76660I interface cards/adapter Internal USB Type-C

Gamintojas: **INLINE** · Modelis: **76660I** · EAN: **4043718341504** · Prekės kodas: **686394**



61,90 €

Kaina su PVM

Be PVM: **51,16 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Connection
- ✓ 1x USB-C socketSpecification
- ✓ USB 3.2 Gen.2x2 with up to 20 Gb/sPCIe 3.0 x4 interface - compatible with x4, x8 and x16 slotsASMedia ASM3242 chipset for high performance and stabilitySupports UASP (USB Attached SCSI Protocol) for optimized data transferPlug & Play functionality - no driver required



Aprašymas

Connection:1x USB-C socket

Specification:USB 3.2 Gen.2x2 with up to 20 Gb/s

PCIe 3.0 x4 interface- compatible with x4, x8 and x16 slots

ASMedia ASM3242 chipsetfor high performance and stability

Supports UASP (USB Attached SCSI Protocol)for optimized data transfer

Plug & Play functionality- no driver required

The **InLine® PCIe interface card**adds a **high-performance USB-C port**with support for the **USB 3.2 Gen.2x2 standard**to your PC. This enables **extremely fast data transfer rates of up to 20 Gb/s-** ideal for **NVMe SSDs, external storage solutions and high-performance peripherals.**

Thanks to the **PCIe 3.0 x4 connection**, the card offers high bandwidth and is compatible with **x4, x8 and x16 slots.** With **Plug & Play**

functionality, modern UASP support and **optimized bandwidth management**, it is a powerful addition to any system.

Technical data:

Bus type & PCIe: PCIe v3.0 (8 GT/s) x4 lane (compatible with x4, x8, x16 slots)

Chip set: ASMedia ASM3242

Power supply via USB-C: Up to 5 V/3 A

Form factor: Low profile

Dimensions: 79 mm x 51 mm (PCIe board)

Supported USB speeds:

SuperSpeed USB: 20 Gb/s, 10 Gb/s, 5 Gb/s

HiSpeed USB: 480 Mb/s

Features:

Plug & Play - no additional drivers required

Supports UASP (USB Attached SCSI Protocol) for optimized data transfer

Overcurrent protection for enhanced security

Optimized bandwidth by supporting multiple INs - ensures a stable and efficient connection

Backwards compatible with older USB standards

Operating system support:

Windows: 11, 10, 8, 7

Windows Server: 2008 R2, 2016, 2019, 2021

Linux: from kernel version 2.6.30

macOS: 10.8 and newer

Environmental conditions:

Operating temperature: 0 °C to 85 °C

Storage temperature: -25 °C to 85 °C

Maximum humidity: 90 %

Scope of delivery:

1x InLine® interface card, PCIe x4, 1x USB-C, USB 3.2 Gen.2x2

1x low-profile slot bracket

1x instruction manual (German/English)

Techninė specifikacija

Specifications

Sandėlio grupė

Server, Storage & Network > Network Adapters [+1948][[-605]

Ports & interfaces

Host interface

PCIe

Output interface

USB Type-C

Host interface gender	Male
Expansion card form factor	Low-profile
Expansion card standard	PCIe 3.0
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	1

Design

Internal	Yes
Country of origin	Taiwan

Features

Chipset	ASMedia ASM3242
Connector 1 gender	Female
Data transfer rate (max)	20 Gbit/s
UASP support	Yes
Plug and Play	Yes

Power

Output voltage	5 V
Output current	3 A

Operational conditions

Operating temperature (T-T)	0 - 85 °C
Storage temperature (T-T)	-25 - 85 °C
Operating relative humidity (H-H)	0 - 90%

System requirements

Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8
Mac operating systems supported	Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura, Mac OS X 14.0 Sonoma, Mac OS X 15.0 Sequoia
Linux operating systems supported	Kernel 2.6.31, Kernel 2.6.33, Kernel 3.12, Kernel 3.17, Kernel 3.3, Kernel 4.6.4, Linux Kernel 5.10, Linux Kernel 5.11, Linux Kernel 5.12, Linux Kernel 5.13, Linux Kernel 5.14, Linux Kernel 5.15, Linux Kernel 5.19, Linux Kernel 5.4, Linux Kernel 5.8, Linux Kernel 5.9, Linux Kernel 6.2, Linux Kernel 6.5
Server operating systems supported	Windows Server 2008 R2, Windows Server 2016, Windows Server 2019, Windows Server 2021

Technical details

Compliance certificates	TÜV mark, Federal Communications Commission (FCC), CE
-------------------------	---

Weight & dimensions

Width	79 mm
Depth	51 mm

Weight	35 g
--------	------

Packaging data

Mounting brackets included	Yes
----------------------------	-----

Manual	Yes
--------	-----

Package weight	35 g
----------------	------

Package type	Hanging box
--------------	-------------