

CyberPower CPS1500PIE uninterruptible power supply (UPS) Double-conversion (Online) 1.5 kVA 1050 W 3 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **CPS1500PIE** · EAN: **4712364141904** · Prekės kodas: **687579**



766,90 €

Kaina su PVM

Be PVM: **633,80 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Double-conversion (Online)
- ✓ 1.5 kVA 1050 W
- ✓ Waveform: Sine
- ✓ 3 AC outlet(s)
- ✓ Sealed Lead Acid (VRLA) 12 V 200 Ah
- ✓ Tower Yellow



Aprašymas

CyberPower Inverter/ Emergency Power System (EPS) utilize state-of-art Microcontroller technology for the supply of lighting, generator, heater, refrigerator, motor, and other apparatus to provide resources during crisis or failure of regular systems. Pure Sinewave output with the adjustable AVR feature is highly flexible to supply continuous power to various types of loads under all kinds of environments. The large LCD panel showcases comprehensive information including load level, battery level, voltage and other vital equipment status with a push-of-a-button.

The competitive design has not only make it the best choice generators but flexible enough to be adopted as UPS for computers and other sensitive equipments.

Techninė specifikacija

Specifications	
Sandėlio grupė	Energy Supply > UPS [+731][-388]
Features	
UPS topology	Double-conversion (Online)
Output power capacity	1.5 kVA
Output power	1050 W
Waveform	Sine
Input operation voltage (min)	140 V
Input operation voltage (max)	300 V
Input frequency	45/65 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	220 V
Output frequency	50/60 Hz
Output frequency regulation	50/60 Hz
Automatic Voltage Regulation (AVR)	Yes
Response time	10 ms
Number of output phases	1
Emergency Power Off (EPO)	Yes
Surge protection	Yes
Power protection features	Over voltage, Overcharge, Overheating, Overload, Reverse polarity
Audible alarm(s)	Yes
Web-based management	No
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm, Battery replacement
Auto-restart	Yes
Ports & interfaces	
AC outlet types	Terminal, Type F
AC outlets quantity	3 AC outlet(s)
Number of type F outputs	2
Battery	
Battery technology	Sealed Lead Acid (VRLA)
Battery capacity	200 Ah
Battery voltage	12 V
Number of batteries supported	10
Charging current	20 A

Hot-swap battery	Yes
Automatic battery test	Yes
Design	
Form factor	Tower
Product colour	Yellow
Display type	LCD
LED indicators	Power
Certificates	
Certification	CE
Packaging content	
Manual	Yes
Weight & dimensions	
Width	261 mm
Depth	206 mm
Height	325 mm
Weight	18.6 kg
Packaging data	
Package type	Box
Other features	
Type of input protection required	3-pole circuit breaker
Bypass	Yes