

APC SRT3000XLW-IEC nepertraukiamo maitinimo resursai (UPS) Dviguba konversija (prisijungus) 3 kVA 2700 W 8 AC išvestis(ys / čių)

 Gamintojas: **APC** · Modelis: **SRT3000XLW-IEC** · EAN: **731304320081** · Prekės kodas: **688598**


4 151,90 €

Kaina su PVM

 Be PVM: **3 431,32 €**


Sandėlyje


Prekė internetu

 Nuskuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Dviguba konversija (prisijungus)
- ✓ 3 kVA 2700 W
- ✓ Signalų forma: Sinusas
- ✓ 8 AC išvestis(ys / čių)
- ✓ Rūgštinis akumulatorius (VRLA)
- ✓ Tower Juoda





Aprašymas

This APC Smart-UPS is designed for IT professionals or network administrators to maintain business uptime and continuity. This 3kVA on-line tower UPS provides pure sine wave power and extended runtime to support critical electronics during power disruptions. It comes with BS1363A British, IEC 320 C20, and Schuko CEE 7/EU1-16P inputs, 6x IEC 320 C13 and 2x IEC 320 C19 outlets. It has a SmartSlot for optional Network Management Card that enables graceful shutdown of physical servers, virtual machines & HCI Clusters via PowerChute Network Shutdown. This On-Line UPS features Unity Power Factor for best-in-class power density. With 10 outlets and a compatibility with external battery packs, this server UPS provides uninterrupted and scalable battery power to connected electronics. The UPS can connect to EcoStruxure IT or third-party centralized management platforms. Use the intuitive LCD interface and PowerChute Business software to configure settings and monitor usage. The UPS has a 3-year warranty, and the built-in lead-acid battery has a 2-year warranty. The UPS is compatible with SRTRK4 (4-post) and SRTRK3 (2-post) rail kits sold separately. A built-in energy meter measures energy use and displays UPS efficiency in various modes of operation for easy energy tracking. Two switchable outlet groups are included for individual load management. Predictive battery management provides an estimated date of when battery replacement is recommended. Package Contains UPS, CD with software, Documentation CD, Installation guide, Removable support feet, Smart UPS signalling RS-232 cable, USB cable.

Techninė specifikacija

Features	
UPS topology	Double-conversion (Online)
Output power capacity	3 kVA
Output power	2700 W
Waveform	Sine
Input operation voltage (min)	100 V
Input operation voltage (max)	275 V
Input frequency	40/70 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Output frequency regulation	50/60 Hz
Surge energy rating	340 J
Efficiency	92.4%
Emergency Power Off (EPO)	Yes
Noise level	55 dB
Surge protection	Yes
Audible alarm(s)	Yes
Web-based management	Yes

Auto-restart	Yes
Ports & interfaces	
AC outlet types	C13 coupler, C19 coupler
Power plug	C20 coupler
AC outlets quantity	8 AC outlet(s)
USB port	Yes
Serial interface	Yes
Serial interface type	RJ-45
SmartSlot	Yes
SmartConnect port	No
Battery	
Battery technology	Sealed Lead Acid (VRLA)
Battery capacity	505 VAh
Typical backup time at full load	4 min
Typical backup time at half load	11.8 min
Battery life (max)	5 year(s)
Battery recharge time	3 h
Hot-swap battery	Yes
Automatic battery test	Yes
Cold start	Yes
Design	
Form factor	Tower
Product colour	Black
Cable length	2.44 m
Display type	LCD
LED indicators	Yes
International Protection (IP) code	IP20
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Certificates	
Compliance certificates	RoHS
Certification	CE, CE Mark, CSA C22.2 No.107.3-05, EAC, EN/IEC 62040-1, EN/IEC 62040-2, FCC Part 15 Class A, RCM, UL 1778, VDE, REACH
Packaging content	
Cables included	RS-232, USB cable
Management card included	No
Quick installation guide	Yes
Sustainability	
Sustainability certificates	ENERGY STAR
Weight & dimensions	
Width	85 mm
Depth	635 mm
Height	432 mm
Weight	31.3 kg
Packaging data	
Software CD	Yes
Package width	599 mm
Package depth	871 mm
Package height	246 mm
Package weight	36.7 kg
Logistics data	
Products per pallet	6 pc(s)
Harmonized System (HS) code	85078000
Total carbon footprint (kg of CO2e)	4961.68
Other features	
Packaging content	Removable support feet

Dokumentai ir vaizdo įrašai

- › Naudojimo instrukcija
- › Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE

rue Joseph Monier 35, 92500 Rueil Malmaison, FR

[se.com](https://www.se.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt