

ATEN 4-Port VGA Video Splitter (450 MHz)

Gamintojas: **ATEN** · Modelis: **VS134A-AT-G** · EAN: **4710423775954** · Prekės kodas: **689036**



146,89 €

Kaina su PVM

Be PVM: **121,40 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ One video input to 4 video outputs
- ✓ Supports up to 450 MHz bandwidth
- ✓ Cascadable to 3 levels - provides up to 64 video signals
- ✓ Long distance transmission - up to 30m
- ✓ Superior video quality - up to 2048 x 1536
- ✓ Supports VGA, XGA, SVGA, UXGA, QXGA, WUXGA and multisync monitors
- ✓ Built-in 1.5 GHz amplifier to ensure video system maintain excellent fidelity
- ✓ All-metal casing



Aprašymas

The VS134A Video Splitter is a boosting device that duplicates a video signal from one source to 4 output devices. Cascadable to three levels, the VS134A provides up to 64 video signals, in addition to extending transmission distance up to 30 m, making it excellent for public broadcast systems. To transmit multiple, high-quality VGA, XGA, SVGA, UXGA, QXGA, WUXGA and multisync video signals over long distance without hassle, the VS134A is your best choice.

Applications include:

- Financial - the remote display of stock market information
- Education - the remote display of lectures and lessons to halls and classrooms
- Business - the remote display of addresses to overflow rooms; video conferencing; and demos

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Switches [+2183][-1086]
Ports & interfaces	
Video ports quantity	5
Video port type	VGA
Video out	4x VGA
DC-in jack	Yes
Features	
Maximum resolution	2048 x 1536 pixels
Product colour	Black
Housing material	Metal
HD type	QXGA
Maximum operating distance	30 m
Bandwidth	450 MHz
LED indicators	Yes
Power	
AC input voltage	5 V
Power consumption (typical)	0.9 W
Weight & dimensions	
Width	75.1 mm
Depth	200 mm
Height	44 mm
Weight	680 g
Packaging data	
Quantity per pack	1 pc(s)
Package width	59 mm
Package depth	239 mm
Package height	160 mm
Package weight	850 g
Packaging content	
Manual	Yes
AC adapter included	Yes

Operational conditions

Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Storage relative humidity (H-H)	0 - 80%

Logistics data

Master (outer) case net weight	13.6 kg
Harmonized System (HS) code	85176990
Master (outer) case width	315 mm
Master (outer) case length	490 mm
Master (outer) case height	338 mm
Master (outer) case gross weight	18 kg
Products per master (outer) case	20 pc(s)