

TP-Link G.hn1200 Powerline Kit

 Gamintojas: **TP-LINK** · Modelis: **PG1200 KIT** · EAN: **4897098687543** · Prekės kodas: **689039**


116,90 €

Kaina su PVM

 Be PVM: **96,61 €**


Sandėlyje


Prekė internetu

 Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Advanced Protocol G.hn - Faster, Stable, Larger Capacity
- ✓ Plug and Play for Whole Home Coverage - Up to 300m over existing electrical wiring
- ✓ 1+1 Gigabit Ethernet Port - Ideal for 8K streaming, lag-free gaming
- ✓ Power Saving Mode - Reduce energy consumption by up to 85%
- ✓ [NOTE] G.hn powerline adapters are not compatible with HomePlug AV/AV2 powerline adapters



Aprašymas

More Reliable

Next-Gen Powerline

G.hn1200 Powerline Kit

Next Generation G.hn Standard

- Significant Speed for Better Performance
- Anti-Interference from Multi-Devices
- Reliable Long Range Transmission

Plug and Play,

Pair for More Security!

1. First, connect your PG1200 to the router
2. Then, plug in another one within 300 meters
3. Finally, press the “Pair” button on each adapter

Wiring up with Gigabit Speeds

Ideal for lag-free gaming and 8K HD Streaming. Just use an Ethernet cable to attach your devices to the Powerline adapter to get started!

Power Save by Up to 85%

PG1200 KIT is a new-generation of Powerline adapter. Its sophisticated Power-Saving mode automatically switches from its regular “Working” mode to “Power-Saving” mode reducing energy consumption by up to 85%.

Techninė specifikacija

Specifications	
Sandėlio grupė	Powerlan [+41][-0]
Performance	
Maximum data transfer rate	607 Mbit/s
Ethernet LAN	Yes
Built-in power socket	No
Ethernet LAN interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Ethernet LAN (RJ-45) ports	2
PowerLine standard	HomePlug AV2
Maximum operating distance	300 m
Design	
Product colour	White
Antenna type	Internal
LED indicators	LAN, Power
System requirements	
Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8, Windows Vista, Windows XP
Linux operating systems supported	Yes
Mac compatibility	Yes
Mac operating systems supported	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width	58 mm

Depth	31.5 mm
Height	88 mm
Packaging data	
Package width	190 mm
Package depth	136 mm
Package height	100 mm
Package weight	230 g
Packaging content	
Quantity per pack	2 pc(s)
Quick installation guide	Yes
Cables included	LAN (RJ-45)
Matmenys ir svoris	
Svoris	0,52kg