

Dahua Technology Access 8-Port Unmanaged Gigabit Switch

Gamintojas: **DAHUA TECHNOLOGY** · Modelis: **DH-PFS3008-8GT-V2** · EAN: **6923172582065** · Prekės kodas: **689060**



73,89 €

Kaina su PVM

Be PVM: **61,07 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Supports eight 10/100/1000 Mbps adaptive ports
- ✓ Easy to operate
- ✓ Small and light, it is easy to carry and has multiple chips embedded in it



Aprašymas

The Device is a layer-2 commercial switch. It has a high-performance switching engine and a large buffer memory to ensure smooth video stream transmission. With a full-metal and fanless design, the Device features great heat dissipation capability on the shell surface. The Device is an unmanaged switch, so it does not need to be configured through web interface, which simplifies installation

Robust Design

Built to last, the architecture of the switch makes it highly reliable, operating with high-efficiency non-stop.

Plug and Play

Hassle-free, it does not require any configuration. Simply use after it is powered on.

Optimized Performance

All ports can transmit streams at high speeds without delay.

Easy Installation

Both desktop and wall mount installation are supported, making it suitable for a wide variety of scenarios.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Switches [+2183][-1086]
Management features	
Switch type	Unmanaged
Switch layer	L2
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Gigabit Ethernet (copper) ports quantity	8
Power connector	DC-in jack
Network	
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-T, 1000BASE-T
Data transmission	
MAC address table	2000 entries
Switching capacity	16 Gbit/s
Forwarding rate	11.904 Mpps
Packet buffer memory	1.5 MB
Design	
Rack mounting	No
Product colour	Black
Housing material	Metal
LED indicators	Yes
Performance	
Mean time between failures (MTBF)	5051758.14 h
Power	
DC input voltage	5 V
Input current	1 A

Power consumption (max)	3 W
-------------------------	-----

Power over Ethernet (PoE)

Power over Ethernet (PoE)	No
---------------------------	----

Operational conditions

Operating temperature (T-T)	0 - 45 °C
-----------------------------	-----------

Storage temperature (T-T)	-40 - 70 °C
---------------------------	-------------

Operating relative humidity (H-H)	5 - 95%
-----------------------------------	---------

Storage relative humidity (H-H)	5 - 95%
---------------------------------	---------

Weight & dimensions

Width	56 mm
-------	-------

Depth	133.5 mm
-------	----------

Height	22 mm
--------	-------

Weight	230 g
--------	-------

Packaging data

AC adapter included	Yes
---------------------	-----

Package width	55 mm
---------------	-------

Package depth	136 mm
---------------	--------

Package height	153 mm
----------------	--------

Package weight	350 g
----------------	-------

Certificates

Compliance certificates	CE, Federal Communications Commission (FCC)
-------------------------	---

Sustainability

Sustainability compliance	Yes
---------------------------	-----

Matmenys ir svoris

Matmenys (l × p × A)	16,00cm × 14,00cm × 6,00cm
----------------------	----------------------------