

Dahua Technology WizSense DH-IPC-HFW2441S-S-0280B security camera Bullet IP security camera Outdoor 2668 x 1520 pixels Wall

Gamintojas: **DAHUA TECHNOLOGY** · Modelis: **DH-IPC-HFW2441SP-S-0280B** · EAN: **6923172539830** · Prekės kodas: **689550**



143,91 €

Kaina su PVM

Be PVM: **118,93 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image
- ✓ Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440@25/30 fps
- ✓ H.265 codec, high compression rate, ultra-low bit rate
- ✓ Built-in IR LED, and the max. illumination distance is 30 m
- ✓ ROI, SMART H.264 +/H.265+, flexible coding, applicable to various bandwidth and storage environments
- ✓ Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- ✓ Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human)
- ✓ Supports max. 256 G Micro SD card; built in MIC
- ✓ 12 VDC/PoE power supply
- ✓ IP67 protection



Aprašymas

Dahua Technology WizSense DH-IPC-HFW2441S-S-0280B. Typ: IP-Sicherheitskamera, Unterstützte Positionierung: Draußen, Übertragungstechnik: Kabelgebunden. Befestigungstyp: Wand, Produktfarbe: Weiß, Formfaktor: Patrone (Form). Drehungswinkel: 360°, Betrachtungswinkel (horizontal): 95°, Betrachtungswinkel (vertikal): 52°. Sensor-Typ: CMOS, Größe des Bildsensors: 25,4 / 2,9 mm (1 / 2.9"). Abstandsbestimmung: 63,6 m, Abstandsbeobachtung: 25,4 m, Abstandserkennung: 12,7 m

Techninė specifikacija

Specifications	
Sandėlio grupė	Netzwerkkameras [+927][[-46]
Performance	
Type	IP security camera
Placement supported	Outdoor
Connectivity technology	Wired
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Dynamic range	120 dB
Design	
Mounting type	Wall
Product colour	White
Form factor	Bullet
Housing material	Metal
International Protection (IP) code	IP67
Camera	
Minimum illumination	0 lx
Angle of rotation	360°
Lens viewing angle, horizontal	95°
Lens viewing angle, vertical	52°
Lens viewing angle, diagonal	114°
Tilt angle range	0 - 90°
Pan range	0 - 360°
White balance	Auto, Manual, Street lamp, Natural
Camera shutter type	Electronic
Camera shutter speed	1/3 - 1/100.000 s
Adjustment shutter speed	Auto/Manual
Number of Privacy masking areas	4
Image sensor	
Sensor type	CMOS
Number of sensors	1
Optical sensor size	25.4 / 2.9 mm (1 / 2.9")
Progressive scan	Yes

Lens system

Detect distance	63.6 m
Observe distance	25.4 m
Recognize distance	12.7 m
Fixed focus	Yes
Identify distance	6.4 m
Minimum aperture number	1.6
Fixed focal length	2.8 mm
Closest focusing distance	0.9 m

Night vision

Night vision	Yes
Night vision distance	30 m
LED type	IR
Number of illumination LEDs	1

Video

Maximum resolution	2668 x 1520 pixels
Total megapixels	4 MP
Video compression formats	H.264, H.264B, H.264H, H.265, M-JPEG
Supported graphics resolutions	352 x 240, 352 x 288, 640 x 480 (VGA), 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2304 x 1296, 2560 x 1440, 2688 x 1520
Video streaming	Yes
Noise reduction	Yes
Noise reduction technology	3D noise reduction
Gain control type	Auto/Manual
Flip & mirror	Yes
Privacy masking	Yes
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Bit rate	12 kbps–6144 kbps
Back Light Compensation (BLC)	Yes
Highlight Compensation (HLC)	Yes
Region of Interest (ROI) encoding	Yes

Audio

Signal-to-Noise Ratio (SNR)	56 dB
Built-in microphone	Yes
Voice codecs	G.711Mu, G.711a, G.726, PCM

Network

Ethernet LAN	Yes
Wi-Fi	No
Bluetooth	No
Ethernet interface type	Fast Ethernet
Supported network protocols	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; NTP; Multicast; ICMP; IGMP
Number of users	6 user(s)
Live view	Yes

Storage

Built-in HDD	No
Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	256 GB
Internal memory	128 MB
ROM capacity	128 MB

Ports & interfaces

Ethernet LAN (RJ-45) ports	1
----------------------------	---

Security

Mirror	Yes
--------	-----

Management features

Web browser	Yes
-------------	-----

Power

Power source type	DC, PoE
Power consumption (typical)	2.5 W
Power consumption (max)	4.2 W
Power consumption (Power over Ethernet (PoE))	3.3 W
DC output voltage	12

Operational conditions

Operating temperature (T-T)	-40 - 60 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	0 - 95%

Weight & dimensions

Width	166.2 mm
-------	----------

Depth	70 mm
Height	70 mm
Weight	480 g
Packaging data	
Package weight	590 g
Packaging content	
Number of cameras	1
Matmenys ir svoris	
Svoris	0,59kg