

Dahua Technology Lite NVR4108HS-4KS2 1U Black

Gamintojas: **DAHUA TECHNOLOGY** · Modelis: **NVR4108HS-4KS2/L** · EAN: **6939554981500** · Prekės kodas: **690748**



186,90 €

Kaina su PVM

Be PVM: **154,46 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ New 4.0 user interface, Security baseline 2.1
- ✓ H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch
- ✓ Max. decoding capability: 8 x 1080p@30 fps. Supports adaptive decoding
- ✓ Supports mainstream cameras of ONVIF and RTSP protocols
- ✓ P2P remote surveillance, video play on mobile device
- ✓ VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K
- ✓ AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD
- ✓ Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches



Techninė specifikacija

Performance

Video input channels	4 channels
Maximum resolution	3840 x 2160 pixels
Supported resolutions	3840x2160, 1920x1080, 1280x1024, 1280x720, 1024x768
Bit rate	20000 Kbit/s

Number of users	128 user(s)
Two-way talk	Yes
People counting	Yes
Video motion detection	Yes
Number of motion detection zones	396
Video loss detection	Yes
Multi-screen	Yes
On Screen Display (OSD)	Yes
Video formats supported	H.264, H.265
PTZ control	Yes
Snapshot	Yes
Playback modes	Backup selection, Digital zoom, Forward, Full screen, Next camera, Pause, Play, Previous camera, Repeat, Reverse, Shuffle, Speed Adjust, Stop
Playback controls	Yes
Throughput data rate	80 Mbit/s
Recording modes	Manual, Schedule, Stop
Recording time	120 min
Wireless LAN features	
Wi-Fi	No
Hard drive	
Maximum storage capacity	6 TB
HDD interface	SATA III
Number of HDDs supported	1
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Power over Ethernet (PoE)	No
Ethernet LAN data rates	10,100,1000 Mbit/s
HDMI output	Yes
HDMI ports quantity	1
VGA (D-Sub) output ports	1
USB 2.0 ports quantity	2
Audio RCA inputs	1
Audio RCA outputs	1
SATA revision	3
Internal SATA ports quantity	1

Supported network protocols	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP
-----------------------------	--

Features

Rack mounting	Yes
Rack capacity	1U
Brand compatibility	Any brand
Product colour	Black
Compatible products	Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec
Certification	CE, FCC, UL, EN55032, EN55024, EN50130-4, EN60950-1, Part 15 Subpart B, ANSI C63.4-2014, UL60950-1+CAN/CSA C22.2 No.60950-1

Processor

Processor cores	4
-----------------	---

Power

Power consumption (typical)	6.3 W
Output current	2 A
Output voltage	12 V

System requirements

Mobile operating systems supported	Android, iOS
------------------------------------	--------------

Operational conditions

Operating temperature (T-T)	-10 - 55 °C
Operating relative humidity (H-H)	0 - 90%
Storage temperature (T-T)	-20 - 70 °C
Storage relative humidity (H-H)	0 - 90%

Weight & dimensions

Width	260 mm
Depth	224.9 mm
Height	47.6 mm
Weight	800 g
Package weight	1.6 kg