

FSP Eufo 2k nepertraukiamo maitinimo resursai (UPS) „Line-Interactive“ 2 kVA 1800 W 8 AC išvestis(ys / čių)

Gamintojas: **FSP GROUP** · Modelis: **PPF16A1500** · EAN: **4711140486130** · Prekės kodas: **690840**



624,90 €

Kaina su PVM

Be PVM: **516,45 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ „Line-Interactive“
- ✓ 2 kVA 1800 W
- ✓ Signalų forma: Gryna sinusoidė
- ✓ 8 AC išvestis(ys / čių)
- ✓ 12 V 9 Ah
- ✓ Stelažas / bokštas Juoda



Aprašymas

FSP Eufo Series rating is from 1.1KVA to 3.0KVA and implemented protect functions for power failures, surge overvoltage and brownout. Rack & Tower with easy-shift LCD design is flexible for installation. Moreover, this series built-in Efficiency corrective Optimizer (ECO) that the efficiency is up to 98% for more energy saving. The application is suitable for networking, telecom, server and mission/critical applications.

Techninė specifikacija

Features	
UPS topology	Line-Interactive
Output power capacity	2 kVA
Output power	1800 W
Waveform	Pure sine
Input operation voltage (min)	162 V
Input operation voltage (max)	290 V
Input frequency	50/60 Hz
Output operation voltage (min)	208 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Output voltage regulation	1.5%
Automatic Voltage Regulation (AVR)	Yes
Response time	6 ms
Efficiency (ECO mode)	97%
Efficiency (Battery mode)	91%
Efficiency (Line Mode)	95%
Power factor	0.99
Crest factor	3:1
Emergency Power Off (EPO)	Yes
Total Harmonic Distortion (THD) (linear load)	2%
Total Harmonic Distortion (THD) (non-linear load)	5%
Noise level	45 dB
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm
Power source type	AC
Detachable power cord	Yes
Ports & interfaces	
AC outlet types	C13 coupler
Power plug	C14 coupler
AC outlets quantity	8 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	1

USB port type	USB Type-B
Serial interface	Yes
Serial interface type	RS-232
RS-232 ports	1
Emergency Power Off (EPO) connector	Yes
SmartSlot	Yes
Battery	
Battery capacity	9 Ah
Battery voltage	12 V
Number of battery cells	4
Battery recharge time	4 h
Battery recharge time(90%)	4 h
Charging current	1.5 A
Hot-swap battery	Yes
Design	
Form factor	Rackmount/Tower
Product colour	Black
Rack capacity	2U
Cooling type	Active
Built-in fan	Yes
Control type	Buttons
Display type	LCD
LED indicators	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	0 - 90%
Certificates	
Compliance certificates	CE, EAC
Packaging content	
Batteries included	Yes
Rack mount kit	Yes
Cables included	Input power cable, USB cable
Weight & dimensions	
Width	438 mm

Depth	510 mm
Height	88 mm
Weight	21.5 kg
Packaging data	
Software CD	Yes
Other features	
Number of phases	1
Packaging content	UPS, user manual, software CD, EU cable, USB cable, tower stands, mounting ears & screws
Sustainability	
Sustainability compliance	Yes

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

FSP Technology Inc.

Xinpu 6th St. No.101, 330 Taoyuan City, TW

fsplifestyle.com

ATSAKINGAS ASMUO ES

Fortron/Source (Europa) GmbH

Carl-Friedrich-Benz-Strasse 13, D-47877 Willich,

DE

fsplifestyle.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt