

CyberPower BPE72V60ART2U UPS battery Sealed Lead Acid (VRLA) 12 V 9 Ah

Gamintojas: **CYBERPOWER** · Modelis: **BPE72V60ART2U** · EAN: **4712364143700** · Prekės kodas: **690974**



1 073,90 €

Kaina su PVM

Be PVM: **887,52 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Black
- ✓ Sealed Lead Acid (VRLA)
- ✓ 12 V
- ✓ 9 Ah
- ✓ 6 pc(s)



Aprašymas

The CyberPower's BPE72V60ART2U Battery Pack significantly extends runtime during power outages for Smart App Online 2K/3k RT models. The BPE72V60ART2U external battery pack houses twelve (12) 12V 9Ah batteries, connected serially in two (2) strings of six (6) batteries. It is designed to match the appearance of the Smart App Online UPS RT models and can be similarly mounted in 2U rack or tower configurations. A battery data link transmits the unit's diagnostic vitals to the UPS display for real-time monitoring; the heavy gauge power cord, adapted with plug-n-play DC connectors, permits the battery pack to be easily "hot-swapped", ensuring continuous operation of critical systems during normal UPS maintenance. Rugged, industrial-grade metal construction - meeting the same standards as the UPS models - allows for installation in demanding environments.

Up to 10 battery packs can be daisy-chained to the UPS for extended runtimes.

Features & Benefits

- Form Factor - 2U configuration supports both rack and tower mounting

- Metal Housing – Rigid metal construction allows for placement in demanding environment.
- Power On/Off Switch - Local power switch for manual reset and control.
- Back-panel fuse- Replaceable fuse is accessible from the rear panel. Must be done by qualified personnel.

Techninė specifikacija

Specifications	
Sandėlio grupė	USV & Stromversorgung [+611][-96]
Features	
Battery technology	Sealed Lead Acid (VRLA)
Battery voltage	12 V
Battery capacity	9 Ah
Number of batteries included	6 pc(s)
Product colour	Black
Hot-swap battery	Yes
Battery recharge time	4 h
Compatibility	OL2000ERTXL2U OL2200ERTXL2U OL3000ERTXL2U
Weight & dimensions	
Weight	44 kg
Width	433 mm
Height	88 mm
Depth	600 mm
Packaging data	
Package width	565 mm
Package height	240 mm
Package depth	880 mm
Package weight	52.7 kg
Package weight	52.7 kg
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 90%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m
Logistics data	

Harmonized System (HS) code	8504909000
-----------------------------	------------

Country of origin	China
-------------------	-------