

TP-Link Tapo C615G KIT Dome IP security camera Outdoor 2304 x 1296 pixels Ceiling/Wall/Pole

Gamintojas: **TP-LINK** · Modelis: **TAPO C615G KIT** · EAN: **8885020629705** · Prekės kodas: **692081**



136,90 €

Kaina su PVM

Be PVM: **113,14 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ **Reliable 4G Connection:** Plug and play with SIM card, ideal for places where constant Wi-Fi is not available.
- ✓ **Solar Charging, Maintenance-Free:** Effortlessly monitor your space wirelessly from any location, liberating yourself from outlet limitations.
- ✓ **Superior 2K 3MP Visuals:** Capture every detail in crystal-clear 2K resolution, with advanced algorithms ensuring perfect exposure day and night.
- ✓ **Free Person/Pet/Vehicle Detection:** The camera identifies people, pets, and vehicles, reducing false alerts and unnecessary notifications.
- ✓ **360° AI Tracking:** The camera provides 360° visual coverage and accurately identifies and tracks people, pets, and vehicles.
- ✓ **Color Night Vision:** See the night in vivid colors with built-in spotlights.
- ✓ **Secure Local & Cloud Storage:** Save crucial moments to a microSD card† (up to 512 GB) or subscribe to Tapo Care for cloud storage after a 30-day free trial, ensuring you never lose important footage.



Aprašymas

Reliable 4G Connection, Plug and Play with SIM Card

Backed by TP-Link's 4G networking expertise, the camera reliably connects through 4G LTE networks. Simply plug in a 4G SIM card (not included) for

an easy, hassle-free internet setup.

Install Anywhere, No Limit to Power and Wi-Fi

Capture the perfect shot while not being limited to power outlet and Wi-Fi, ideals for places like farms, campsites, construction sites and vacation homes. Combine the camera and solar panel into one sleek unit for a neater appearance or connect via a 4-meter cable to maximize sun exposure.

Solar Charging, Wire-Free, Maintenance-Free

45 Minutes of Direct Sunlight

powers the Tapo C615G camera for a full day, eliminating battery concerns and staying green.

120-Day Battery Life

lasts long on a single charge, guaranteeing continuous performance even without sunlight.

See in 2K Clarity, Day and Night

The camera offers enhanced video quality with 2K resolution. Enjoy colorful images in low-light conditions at night with built-in spotlights.

360° All-Round Protection

Enhance your security with 360° horizontal & 134° vertical viewing range. Set the camera to scan scheduled 360° rotations and capture panoramic videos, or have it patrol key points at set times and record only when motion is detected.

Free AI Detections and Tracking

Smart AI identifies and tracks people, pets, and vehicles, reducing irrelevant notification and sending alerts only when necessary.

Sound and Light Alarm

Deter unwelcomed intruders with customizable audio and tailor the intensity of the dual spotlights for fine-tuned illumination.

Designed to Resist Harsh Weather

With IP65 weatherproofing, Tapo C615G KIT offers excellent waterproof and dustproof performance for outdoor scenarios. It works well in rain, dust, and heat, operating reliably in different environments.

Secure Local Recording & Cloud Storage

Save all your important moments to a microSD card (up to 512 GB) or subscribe to Tapo Care+ for cloud service after a free trial.

Local microSD Storage

The camera supports up to 512GB of free local storage. Secure your microSD card with a password through the Tapo app for enhanced privacy protection.

Tapo Care Cloud Storage

Receive notifications with detection snapshots, encrypted protection, data backups, and 30-day video clip history with Tapo Care cloud services.

Techninė specifikacija

Specifications	
Sandėlio grupė	Netzwerkkameras [+927][(-46)]
Performance	
Type	IP security camera
Placement supported	Outdoor
Connectivity technology	Wireless

Auto-tracking	Yes
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Built-in light	Yes
Design	
Mounting type	Ceiling/Wall/Pole
Product colour	White
Form factor	Dome
International Protection (IP) code	IP65
Camera	
Camera pan control	Yes
Camera tilt control	Yes
Lens viewing angle, horizontal	84.4°
Lens viewing angle, vertical	44.3°
Lens viewing angle, diagonal	100.6°
Image sensor	
Sensor type	CMOS
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")
Progressive scan	Yes
Lens system	
Number of lenses	1
Zoom capability	Yes
Digital zoom	10.8x
Maximum aperture number	1.6
Fixed focal length	4 mm
Night vision	
Night vision	Yes
LED type	IR
Infra-red wavelength	850 nm
Video	
Maximum resolution	2304 x 1296 pixels
Total megapixels	3 MP
Noise reduction	Yes
Noise reduction technology	3D noise reduction

Audio

Built-in speaker(s)	Yes
Audio system	2-way
Built-in microphone	Yes

Network

Ethernet LAN	No
Wi-Fi	No
Bluetooth	No
SIM card slot	Yes
SIM card type	NanoSIM
Mobile network connection	Yes
Mobile network generation	4G
4G standard	LTE-TDD & LTE-FDD

Storage

Built-in HDD	No
Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	512 GB

Security

Built-in siren	Yes
Siren noise level	98.6 dB
Video motion detection	Yes
Security algorithms	SSL/TLS
Intelligent Video Surveillance (IVS) system features	Human detection, Pet detection, Vehicle detection

Management features

Cloud-managed	Yes
Reset button	Yes

Power

Power source type	AC, Battery, Solar
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
DC output voltage	5
Battery technology	Lithium-Ion (Li-Ion)
Battery capacity	6700 mAh

Rechargeable battery	Yes
----------------------	-----

Operational conditions

Operating temperature (T-T)	-20 - 45 °C
-----------------------------	-------------

Storage temperature (T-T)	-40 - 60 °C
---------------------------	-------------

Operating relative humidity (H-H)	10 - 90%
-----------------------------------	----------

Storage relative humidity (H-H)	0 - 90%
---------------------------------	---------

Weight & dimensions

Width	130.9 mm
-------	----------

Depth	116.1 mm
-------	----------

Height	84.1 mm
--------	---------

Weight	451 g
--------	-------

Sustainability

Compliance certificates	CE, RCM
-------------------------	---------

Packaging content

Number of cameras	1
-------------------	---

Mounting kit	Yes
--------------	-----

Drilling template included	Yes
----------------------------	-----

Matmenys ir svoris

Matmenys (I × P × A)	20,00cm × 24,00cm × 15,00cm
----------------------	-----------------------------

Svoris	1,35kg
--------	--------