FSP Champ Tower 2K uninterruptible power supply (UPS) Double-conversion (Online) 2 kVA 1800 W

Gamintojas: **FSP** · Modelis: **PPF16A1905** · EAN: **4711140487601** · Prekės kodas: **692661**

425,90 €

Kaina su PVM

Be PVM: **351,98 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ True double-conversion
- ✓ Excellent microprocessor control for high reliability
- ✓ Input power factor correction
- ✓ Output power factor 0.9
- ✓ Wide input voltage (120 V – 300 V)
- ✓ Converter mode available
- ✓ ECO mode for energy saving
- ✓ Generator compatible
- ✓ Charger capacity expansion to 6A for long-run models
- ✓ Smart SNMP works well with either USB or RS-232 together

Aprašymas

FSP Champ Tower Series is the high density version of double-conversion online UPS with a output power factor 0.9. It’s designed in small cabinet with microprocessor controller. It also has USB and RS-232 communication ports as standard, with a built-in intelligent slot for additional adapters, protocol converters and relate contact cards.

Techninė specifikacija

Specifications

Sandėlio grupė	USV & Stromversorgung [+611][-96]
Features	
UPS topology	Double-conversion (Online)
Output power capacity	2 kVA
Output power	1800 W
Waveform	Sine
Input operation voltage (min)	120 V
Input operation voltage (max)	300 V
Input frequency	40 - 70 Hz
Output operation voltage (min)	200 V
Output operation voltage (max)	240 V
Output frequency	47/63 Hz
Output voltage regulation	1%
Response time	0 ms
Power factor	0.99
Crest factor	3:1
Total Harmonic Distortion (THD) (linear load)	3%
Total Harmonic Distortion (THD) (non-linear load)	6%
Noise level	50 dB
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm
Ports & interfaces	
AC outlet types	C13 coupler
Number of output IEC jumpers	4
USB port	Yes
USB 2.0 ports quantity	1
USB port type	USB Type-B
Serial interface	Yes
Serial interface type	RS-232
RS-232 ports	1
Battery	
Battery capacity	9 Ah
Battery voltage	12 V
Number of battery cells	4
Typical backup time at full load	3.5 min

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Typical backup time at half load	9.6 min
Battery recharge time(90%)	4 h
Design	
Form factor	Tower
Product colour	Black
Control type	Buttons
Display type	LCD
LED indicators	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 90%
Packaging content	
Batteries included	Yes
Cables included	Input power cable, USB cable
Manual	Yes
Weight & dimensions	
Width	145 mm
Depth	397 mm
Height	220 mm
Weight	17 kg
Packaging data	
Software CD	Yes
Logistics data	
Harmonized System (HS) code	85078000
Other features	
Number of phases	1
Packaging content	UPS, Power cable, USB cable, Software on CD, User manual
Matmenys ir svoris	
Matmenys (I × P × A)	48,00cm × 24,00cm × 32,00cm
Svoris	18,40kg

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903