

ATEN 16P Short Depth Single Rail LCD KVM SW

Gamintojas: **ATEN** · Modelis: **CL3116NX** · EAN: **4719264648984** · Prekės kodas: **693011**



1 942,90 €

Kaina su PVM

Be PVM: **1 605,70 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Exclusive LED illumination light
- ✓ Integrated LCD KVM console with an 18.5" LED-backlit widescreen LCD monitor in a single rail housing with top and bottom clearance for smooth operation in a 1U high system rack
- ✓ Cascade up to 2 levels – CL3116 controls up to 256 computers from a single console
- ✓ Keyboard and mouse emulation (PS/2 and USB) for smooth switching and simultaneously booting multiple computers even when the console focus is elsewhere



Aprašymas

The ATEN CL3116 LCD KVM Switch offers a space-saving, streamlined approach to KVM switch technology by integrating a keyboard, 18.5" LED-backlit LCD monitor, and a touchpad in a 1U rack-mountable sliding housing. The short-depth design maximizes space utility for equipping rack-mounting devices in narrow spaces. In addition, its exclusive LED illumination light provides users with proper visibility when working in low-light conditions.

- 1x CL3116 LCD KVM Switch with Standard Rack Mounting Kit
- 2x LIN5-15X3-U12G Custom KVM Cables (VGA, USB; 1.8m/6ft)
- 1x LIN5-004A2-J15G Firmware Upgrade Cable
- 1x LIN2-418K-E12G Power Cord
- 1x User Instructions

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Switches [+2183][-1086]
Display	
Display diagonal	47 cm (18.5")
Display resolution	1366 x 768 pixels
Display	TFT-LCD
Display brightness	250 cd/m²
Contrast ratio (typical)	1000:1
Viewing angle, horizontal	170°
Viewing angle, vertical	160°
On Screen Display (OSD)	Yes
Pixel pitch	0.3 x 0.3 mm
Display type	LED
Display number of colours	16.78 million colours
Technical details	
Rack capacity	1U
Material	Metal, Plastic
Plug and Play	Yes
Product colour	Black
Hot-Plug support	Yes
Operating relative humidity (H-H)	0 - 80%
Built-in KVM switch	Yes
KVM switch ports quantity	16
Maximum resolution	1366 x 768 pixels
Rack mounting	Yes
Number of computers controlled	16
LED indicators	Yes
Push button	Yes
Ports & interfaces	
3.5 mm (1/8-inch) in	Yes
Mouse port type	USB, PS/2
Video port type	VGA
Keyboard	

Keyboard language	US English
Keyboard layout	QWERTY
Hot keys	Yes
Power	
Power supply type	AC
AC adapter input voltage	100 - 240 V
AC adapter frequency	50 / 60 Hz
Input current	1 A
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Weight & dimensions	
Width	480.6 mm
Height	631.7 mm
Depth	42.8 mm
Weight	11.1 kg
Packaging data	
Package weight	13.9 kg
Package width	668 mm
Package depth	718 mm
Package height	135 mm
Logistics data	
Master (outer) case net weight	11.1 kg
Master (outer) case width	668 mm
Master (outer) case length	718 mm
Master (outer) case height	135 mm
Master (outer) case gross weight	13.9 kg
Products per master (outer) case	1 pc(s)