

ATEN 16-Port 19" LCD Cat5e/6 KVM Over IP Switch (Dual Rail)

Gamintojas: **ATEN** · Modelis: **KL1516AIN-AX-XG** · EAN: **4719264642623** · Prekės kodas: **693067**



3 589,90 €

Kaina su PVM

Be PVM: **2 966,86 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Exclusive LED illumination light - designed by ATEN to illuminate the keyboard and touchpad to allow visibility in low-light conditions
- ✓ Dual Rail – LCD monitor slides independently of the keyboard/touchpad
- ✓ One local/remote share access bus –allowing IT administrators to monitor and control up to 16 servers
- ✓ Superior Video Quality – supports input video resolutions up to 1920 x 1200 @ 60Hz** up to 30 meters, 1600 x 1200 @ 60Hz up to 40 meters, and 1280 x 1024 @ 75Hz up to 50 meters



Aprašymas

The KL1516Ai Dual Rail LCD KVM Switch is a control unit that allows secure access up to 16 computers from a single KVM (keyboard, video, and mouse) console. It consists of an integrated LCD monitor, keyboard, and touchpad in a 1U rack-mountable retractable sliding housing.

The LCD and keyboard/touchpad modules slide independently of each other. To maximize space in your data center, the keyboard/touchpad module slides back to "hide away" when not in use, while the thin profile LCD monitor rotates back – flush against the rack – allowing convenient monitoring of computer activity.

The KL1516Ai features IP-based connectivity that allows local and remote operators to monitor and access the computers on your installation. Because it uses TCP/IP for its communications protocol, the KL1516Ai can be accessed from any computer on the LAN, WAN, or Internet – whether that computer is located down the hall, down the street, or halfway around the world.

1x KL1516Ai Dual Rail LCD KVM Switch

1x LIN2-418K-E12G Power Cord
1x Standard Rack Mount Kit
1x LINS-04A2-J11G Firmware Upgrade Cable
2x L Brackets
1x User Instructions

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Switches [+2183][-1086]
Display	
Display diagonal	48.3 cm (19")
Display	LCD
On Screen Display (OSD)	Yes
Technical details	
Rack capacity	1U
Product colour	Black
Operating relative humidity (H-H)	0 - 80%
Maximum resolution	1920 x 1200 pixels
Networking standards	IEEE 802.3, IEEE 802.3u
Rack mounting	Yes
Daisy chain	Yes
Number of computers controlled	16
LED indicators	Yes
Push button	Yes
Cabling technology	10/100Base-T(X)
Ports & interfaces	
VGA (D-Sub) ports quantity	1
Keyboard port type	USB, PS/2
Mouse port type	USB, PS/2
Video port type	VGA
Keyboard	
Keyboard language	US English
Keyboard layout	QWERTY
Hot keys	Yes
Power	
Power consumption (typical)	36 W

Input current	1 A
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
System requirements	
Windows operating systems supported	Yes
Weight & dimensions	
Width	480 mm
Height	44 mm
Depth	701.2 mm
Weight	15.7 kg
Packaging data	
Package weight	18.8 kg
Package width	668 mm
Package depth	833 mm
Package height	135 mm
Packaging content	
Quick installation guide	Yes
Manual	Yes
Logistics data	
Master (outer) case net weight	15.7 kg
Master (outer) case width	668 mm
Master (outer) case length	833 mm
Master (outer) case height	135 mm
Master (outer) case gross weight	18.8 kg
Products per master (outer) case	1 pc(s)