

LevelOne UPS-2103 uninterruptible power supply (UPS) Double-conversion (Online) 3 kVA 3000 W 8 AC outlet(s)

Gamintojas: **LEVEL ONE** · Modelis: **UPS-2103** · EAN: **4015867235034** · Prekės kodas: **693467**



1 245,90 €

Kaina su PVM

Be PVM: **1 029,67 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ True double-conversion design with high adaptability to harsh mains conditions.
- ✓ Real PF 1 can provide more power in same space High efficiency results in energy saving.
- ✓ Adjustable charging current and flexible battery configuration .
- ✓ Optimized changing method to expand battery life time.
- ✓ Built-in OVCD protection, fan lock detection, over temperature detection, overload warning to enhance the product reliabilit.
- ✓ Dot matrix LCD support up to 10 languages for easy installation and service.(Included 8 languages, with 2 additional customizable options).
- ✓ Embedded Ethernet port solution provide safe network connection to Cloud which will meet the increasing IoT trend. Mobile APP for monitoring, Support Android/iOS.
- ✓ USB HID enable monitoring on UPS without software installation.
- ✓ Dry contactor for industrial condition.
- ✓ Free Management Software monitor Max to 1000 unit UPS



Aprašymas

The LevelOne Online UPS is the ultimate solution for dependable battery backup in both home and office settings. With an output power factor of 1.0, this UPS delivers maximum efficiency and performance. Designed for generator compatibility, it provides continuous power even during extended outages. Equipped with a HID-compatible USB connection for seamless device communication and an Emergency Power Off (EPO) port for added safety during emergencies, the UPS offers both convenience and security. The easy battery replacement feature simplifies maintenance, while

the programmable outlet management allows you to tailor power distribution to meet your specific needs. Easy to install and operate, the LevelOne Online UPS provides a reliable and efficient way to protect your systems from power surges and failures, ensuring the uninterrupted operation of your critical equipment. The included rackmount ears support both rack mounting and tower installation, offering flexibility in setup.

Techninė specifikacija

Specifications	
Sandėlio grupė	USV & Stromversorgung [+611][-96]
Features	
UPS topology	Double-conversion (Online)
Output power capacity	3 kVA
Output power	3000 W
Waveform	Sine
Input operation voltage (min)	160 V
Input operation voltage (max)	300 V
Input frequency	50/60 Hz
Output operation voltage (min)	200 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Power factor	1
Emergency Power Off (EPO)	Yes
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm
Ports & interfaces	
AC outlet types	C13 coupler, C19 coupler
AC outlets quantity	8 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	1
USB port type	USB Type-B
Serial interface	Yes
Serial interface type	RS-232
Serial ports quantity	1
RS-232 ports	1
Ethernet LAN (RJ-45) ports	2
Emergency Power Off (EPO) connector	Yes
Battery	

Battery technology	Lead-Acid
Battery capacity	9000 Ah
Battery voltage	72 V
Number of batteries included	6 pc(s)
Battery recharge time(90%)	3 h
Battery capacity	108 Wh
Rechargeable battery	Yes
Design	
Form factor	Rackmount/Tower
Product colour	Black
Control type	Buttons
Display type	LCD
International Protection (IP) code	IP20
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	0 - 90%
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
Packaging content	
Batteries included	Yes
Rack mount kit	Yes
Cables included	Input power cable, USB cable
Manual	Yes
Quick installation guide	Yes
Weight & dimensions	
Width	600 mm
Depth	438 mm
Height	85.5 mm
Weight	26.3 kg
Packaging data	
Package type	Box
Matmenys ir svoris	
Svoris	30,50kg