

ASUS PRIME N100I-D D4 NA (integrated CPU) mini ITX

Gamintojas: **ASUS** · Modelis: **90MB1F70-M0EAYC** · EAN: **4711387262320** · Prekės kodas: **693511**



253,89 €

Kaina su PVM

Be PVM: **209,83 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Ultrafast Connectivity: PCIe 3.0 x1 slot, 16Gbps M.2 support, rear USB 3.2 Gen 2, front USB 3.2 Gen 1 and 1Gb Ethernet
- ✓ Comprehensive Cooling: CPU heatsink
- ✓ Better serviceability: COM debug header to facilitate building and support processes



Aprašymas

N100I-D D4

ASUS Prime series motherboards are expertly engineered to unleash the full potential of Intel® Processor N100. Boasting a robust power design, comprehensive cooling solutions and intelligent tuning options, PRIME N100I-D D4 provides users and PC DIY builders with a range of performance optimizations via intuitive software and firmware features.

COOLING

PRIME N100I-D D4 engineered with onboard CPU heatsink and a chassis fan header to ensure your rig stays cool and stable under intense workloads.

CPU Heatsink and Thermal Pad

CPU heatsink and thermal pad improve heat transfer from the CPU for better cooling performance.

PERFORMANCE

ASUS N100 motherboard provides all the fundamentals to boost daily productivity, so your system will be ready for action with stable power,

intuitive cooling and flexible data transfer options.

Techninė specifikacija

Specifications	
Sandėlio grupė	Components & Accessories > Mainboards/Systemboards [+7036][-7603]
Processor	
Processor manufacturer	Intel
Processor socket	NA (integrated CPU)
Compatible processor series	Intel Processor N
Processor model	N100
Processor cores	4
Maximum internal memory supported by processor	16 GB
Memory	
Supported memory types	DDR4-SDRAM
Number of memory slots	1
Maximum internal memory	16 GB
Memory slots type	SO-DIMM
ECC compatibility	Non-ECC
Supported memory clock speeds	2133,2400,2666,2800,2933,3200 MHz
Supported memory clock speed (max)	3200 MHz
Unbuffered memory	Yes
Storage controllers	
Supported storage drive interfaces	M.2, SATA III
Supported storage drive types	HDD & SSD
Number of HDDs supported	1
Number of storage drives supported	2
Graphics	
Parallel processing technology support	Not supported
Internal I/O	
USB 2.0 connectors	1
USB 3.2 Gen 1 (3.1 Gen 1) connectors	1
USB 3.2 Gen 2 (3.1 Gen 2) connectors	0
Number of SATA III connectors	1
S/PDIF out connector	Yes

Audio connector	Yes
Front panel audio connector	Yes
ATX Power connector (24-pin)	Yes
Number of chassis fan connectors	1
Peripheral (Molex) power connectors (4-pin)	1
Number of COM connectors	1
TPM connector	Yes
12V power connector	Yes
Rear panel I/O ports	
USB 2.0 ports quantity	2
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	0
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	2
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	0
Ethernet LAN (RJ-45) ports	1
VGA (D-Sub) ports quantity	1
HDMI ports quantity	1
DVI-D ports quantity	0
PS/2 ports quantity	1
DisplayPorts quantity	1
Headphone outputs	1
Line-in	Yes
Microphone in	Yes
COM ports quantity	1
Network	
Wi-Fi	No
Ethernet LAN	Yes
Ethernet interface type	Gigabit Ethernet
Features	
Component for	PC
Motherboard form factor	mini ITX
Motherboard chipset family	Intel
Audio output channels	7.1 channels
Windows operating systems supported	Windows 10 x64, Windows 11

Expansion slots	
PCI Express x1 (Gen 3.x) slots	1
Number of M.2 (M) slots	1
BIOS	
BIOS type	UEFI AMI
BIOS memory size	128 Mbit
Packaging data	
Package width	227 mm
Package depth	185 mm
Package height	60 mm
Package weight	664 g
Weight & dimensions	
Width	170 mm
Depth	170 mm
Packaging content	
Cables included	SATA