

CyberPower OLS3000ERT2UA uninterruptible power supply (UPS) Double-conversion (Online) 2 kVA 1800 W 8 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **OLS3000ERT2UA** · EAN: **4712856273823** · Prekės kodas: **696290**



660,90 €

Kaina su PVM

Be PVM: **546,20 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Online (Double Conversion) UPS Topology
- ✓ Generator Compatible
- ✓ Zero Transfer Time
- ✓ Extended Battery Module Auto-detection
- ✓ Critical/Non-critical Load Outlets
- ✓ Phone/Fax/Modem/DSL/Network Protection
- ✓ Variable Speed Fans
- ✓ PowerPanel Management Software
- ✓ Rack/Tower Convertible Configurations
- ✓ ECO Mode



Aprašymas

CyberPower OLS2000ERT2UA is a high-performance UPS featuring online double-conversion topology, which provides seamless Pure Sine Wave power for mission-critical devices such as NAS and servers, DVRs/surveillance systems, transportation and infrastructure, and emergency systems. It's typically integrated in the back office, server room, and data center environment.

The UPS features color LCD panel for users to monitor power system and configure settings easily. This model can be used with compatible Extended Battery Modules (EBM) to prolong system runtime during power interruption. The variable speed fans provide automatic thermal management based on power load to reduce noise and provide greater comfort for users. The product also supports power management software to perform real-time monitoring and remote management.

Techninė specifikacija

Specifications	
Sandėlio grupė	USV & Stromversorgung [+611][-96]
Features	
UPS topology	Double-conversion (Online)
Output power capacity	2 kVA
Output power	1800 W
Waveform	Pure sine
Input operation voltage (min)	190 V
Input operation voltage (max)	300 V
Input frequency	50/60 Hz
Output operation voltage (min)	208 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Output frequency regulation	0.5 Hz
Output voltage regulation	1%
Maximum current	9 A
Surge energy rating	363 J
Response time	0 ms
Heat dissipation	682 BTU/h
Efficiency (ECO mode)	95%
Power factor	0.9
Input power factor	0.99
Output power factor	0.9
Crest factor	3:1
ECO mode	Yes
Emergency Power Off (EPO)	Yes
Output voltage Total Harmonic Distortion (THD)	5%
EMI/RFI noise filtering	Yes
Surge protection	Yes
Power protection features	Overload
Audible alarm(s)	Yes
Audible alarm modes	Battery replacement, Low battery alarm, Overload alarm, Fault, Alarm when on battery
Ports & interfaces	

AC outlet types	C13 coupler
Power plug	Type F
AC outlets quantity	8 AC outlet(s)
USB port	Yes
USB port type	USB Type-B
Serial interface	Yes
Serial interface type	RS-232
Serial ports quantity	1
RS-232 ports	1
Modem (RJ-11) ports	1
Ethernet LAN (RJ-45) ports	1
Emergency Power Off (EPO) connector	Yes
Battery	
Battery technology	Sealed Lead Acid (VRLA)
Battery capacity	9 Ah
Battery voltage	48 V
Number of batteries supported	3
Number of batteries included	2 pc(s)
Typical backup time at full load	3.8 min
Typical backup time at half load	13.1 min
Battery life (max)	5 year(s)
Battery recharge time	4 h
Charging current	1.5 A
Hot-swap battery	Yes
Replacement battery cartridge	RBP0157
Design	
Form factor	Rackmount/Tower
Product colour	Black
Housing material	Metal
Rack capacity	2U
Cable length	1.5 m
Cooling type	Active
Built-in fan	Yes
Control type	Buttons
Display type	LCD

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 50 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	-20 - 50%
Operating altitude	0 - 1500 m
Non-operating altitude	0 - 1500 m

Certificates

Compliance certificates	CE, EAC, RoHS
Certification	CE, EAC

Packaging content

Batteries included	Yes
Rack mount kit	Yes
Cables included	Input power cable, USB cable
Manual	Yes

Weight & dimensions

Width	438 mm
Depth	430 mm
Height	88 mm
Weight	19.2 kg

Packaging data

Package width	540 mm
Package depth	550 mm
Package height	230 mm
Package weight	23.4 kg

Logistics data

Harmonized System (HS) code	8504408590
Country of origin	China

Matmenys ir svoris

Matmenys (l × p × A)	75,00cm × 55,00cm × 23,00cm
----------------------	-----------------------------