

FSP Champ Tower 3K uninterruptible power supply (UPS) Double-conversion (Online) 3 kVA 2700 W

Gamintojas: **FSP GROUP** · Modelis: **PPF24A1823** · EAN: **4713224529856** · Prekės kodas: **696565**



671,90 €

Kaina su PVM

Be PVM: **555,29 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ True double-conversion
- ✓ Microprocessor control optimizes reliability
- ✓ Input power factor correction
- ✓ Output power factor 0.9
- ✓ Wide input voltage (120 V – 300 V)
- ✓ Converter mode available
- ✓ ECO mode for energy saving
- ✓ Generator compatible
- ✓ Charger capacity expansion to 6A for long-run models
- ✓ Smart SNMP works well with either USB or RS-232 together



Aprašymas

FSP Champ is the high density version of double-conversion online UPS with a output power factor 0.9. It's designed in small cabinet with microprocessor controller.

Champ also have USB and RS-232 communication ports as standard, with a built-in intelligent slot for additional adapters, protocol converters and relate contact cards.

Techninė specifikacija

Specifications

Sandėlio grupė Energy Supply > UPS [+731][-388]

Features

UPS topology	Double-conversion (Online)
Output power capacity	3 kVA
Output power	2700 W
Waveform	Pure sine
Input operation voltage (min)	120 V
Input operation voltage (max)	300 V
Input frequency	40 - 70 Hz
Output operation voltage (min)	200 V
Output operation voltage (max)	240 V
Output frequency	47/63 Hz
Output voltage regulation	1%
Response time	0 ms
Power factor	0.99
Crest factor	3:1
Noise level	50 dB
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm

Ports & interfaces

AC outlet types	Type F
Number of output IEC jumpers	4
USB port	Yes
USB 2.0 ports quantity	1
USB port type	USB Type-B
Serial interface	Yes
Serial interface type	RS-232
RS-232 ports	1

Battery

Battery capacity	9 Ah
Battery voltage	12 V
Number of battery cells	6
Typical backup time at full load	3.5 min

Typical backup time at half load	9.8 min
----------------------------------	---------

Design

Form factor	Rackmount/Tower
-------------	-----------------

Product colour	Black
----------------	-------

Control type	Buttons
--------------	---------

Display type	LCD
--------------	-----

LED indicators	Yes
----------------	-----

Operational conditions

Operating temperature (T-T)	0 - 40 °C
-----------------------------	-----------

Operating relative humidity (H-H)	20 - 90%
-----------------------------------	----------

Packaging content

Batteries included	Yes
--------------------	-----

Cables included	Input power cable, USB cable
-----------------	------------------------------

Manual	Yes
--------	-----

Weight & dimensions

Width	190 mm
-------	--------

Depth	421 mm
-------	--------

Height	318 mm
--------	--------

Weight	27.6 kg
--------	---------

Matmenys ir svoris

Matmenys (I × P × A)	40,00cm × 15,00cm × 23,00cm
----------------------	-----------------------------