

TP-Link ES206XPP-M2 network switch Managed L2 2.5G Ethernet (100/1000/2500) Power over Ethernet (PoE) Desktop/Wall-Mounting Black

Gamintojas: **TP-LINK** · Modelis: **ES206XPP-M2** · EAN: **1210002600965** · Prekės kodas: **697273**



266,90 €

Kaina su PVM

Be PVM: **220,58 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 5x 2.5 Gbps RJ45 ports (4x 802.3af/at/bt-compliant PoE++)
- ✓ 1x 10 Gbps SFP+ slot
- ✓ 120W PoE budget, with up to 90W for each PoE port*
- ✓ Easy to Use: Supports plug-and-play for instant connectivity and simple configuration for additional features
- ✓ Centralized Cloud Management via the web or the Omada app†
- ✓ Automatic Loop Prevention, VLAN, Port Isolation, QoS, and IGMP Snooping
- ✓ Fanless design for silent operation
- ✓ Durable metal casing and desktop/wall mounting design



Aprašymas

Power over Ethernet, Flexible Network Deployment

Transmit both data and power via a single cable to other PoE++ devices, without the hassle and cost of installing power cabling. Automatically detect and supply the required power to PoE-enabled devices.

Works with Omada Central Essentials for Free and Easy Cloud Management

Omada Central Essentials provides free and easy-to-use centralized cloud management and monitoring for the Omada networking system, covering access points, switches, and gateways, ideal for small businesses and home office.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Switches [+2183][-1086]
Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	5
Basic switching RJ-45 Ethernet ports type	2.5G Ethernet (100/1000/2500)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
SFP+ module slots quantity	1
Network	
Networking standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3bz, IEEE 802.3z, IEEE 802.3ae, IEEE 802.3aq, IEEE 802.3x, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1ab
10G support	No
Port mirroring	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
VLAN support	Yes
Virtual LAN features	MTU VLAN, Port-based VLAN
Data transmission	
MAC address table	16000 entries
Switching capacity	45 Gbit/s
Forwarding rate	33.48 Mpps
Store-and-forward	Yes
Jumbo frames support	Yes
Jumbo frames	10
Packet buffer memory	0.64 MB
Security	
DHCP features	DHCP client
IGMP snooping	Yes

Design	
Form factor	Desktop/Wall-Mounting
Product colour	Black
LED indicators	Yes
Performance	
Flash memory	64 MB
Firmware upgradeable	Yes
Power	
Power source	AC/PoE
Power supply included	Yes
AC input voltage	100 - 240 V
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) type supported	PoE++ (4PPoE)
Power over Ethernet 4PPoE (PoE++) ports quantity	4
Power over Ethernet (PoE) power per port	90 W
Total Power over Ethernet (PoE) budget	120 W
Operational conditions	
Operating temperature (T-T)	-5 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	209 mm
Depth	126 mm
Height	26 mm
Certificates	
Certification	CE, FCC, RoHS