CyberPower Online S Series Online Double Conversion USV 1000VA/900WTower, ECO Mode, LCD, USB, Smart-Slot

Gamintojas: **CYBERPOWER** · Modelis: **OLS1KECR** · EAN: **4711027792606** · Prekės kodas: **697470**

398,90 €

Kaina su PVM

Be PVM: **329,67 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Online (Double Conversion) UPS Topology
- ✓ Generator Compatible
- ✓ Zero Transfer Time
- ✓ Extended Battery Module (EBM)
- ✓ EMI and RFI Filtration
- ✓ Relay-type Dry Contact
- ✓ Variable Speed Fans
- ✓ PowerPanel Cloud Service
- ✓ ECO Mode
- ✓ Overload Protection

Aprašymas

CyberPower OLS1KECR provides reliable battery backup and power protection for multimedia devices, IT equipment, computers, workstations, NAS/Storage devices, telecom devices, networking devices, security/emergency systems, and surveillance systems. The UPS adopts double-conversion topology to provide optimal power quality as well as ECO Mode to conserve power and save on energy costs. Furthermore, the product is generator compatible to achieve power continuity and designed with Smart Battery Management (SBM) to extend battery lifespan.

In order to reduce noise and ensure greater comfort for users, the UPS is equipped with variable speed fans to provide automatic thermal management based on power load. The color LCD panel displays intuitive and clear system information, allowing users to monitor and configure settings easily. The product can be used with PowerPanel Management Software to achieve real-time monitoring and remote management of the

UPS.

Techninė specifikacija

Specifications	
Sandėlio grupė	Energy Supply > UPS [+731][-388]
Features	
UPS topology	Double-conversion (Online)
Output power capacity	1 kVA
Output power	900 W
Waveform	Pure sine
Input operation voltage (min)	80 V
Input operation voltage (max)	300 V
Input frequency	50/60 Hz
Output operation voltage (min)	208 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Output voltage regulation	1%
Automatic Voltage Regulation (AVR)	Yes
Maximum current	4.5 A
Surge energy rating	370 J
Heat dissipation	380 BTU/h
Efficiency (ECO mode)	95%
Input power factor	0.99
Output power factor	0.9
Crest factor	3:1
ECO mode	Yes
Emergency Power Off (EPO)	Yes
Overload capacity (1 minute)	120%
Overload capacity (10 seconds)	120%
Output voltage Total Harmonic Distortion (THD)	5%
EMI/RFI noise filtering	Yes
Surge protection	Yes
Power protection features	Input fuse, Overload
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm, Fault, Battery replacement

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Socket circuit breaker	Yes
Ports & interfaces	
AC outlet types	C13 coupler, Type F
Power plug	Type F
AC outlets quantity	3 AC outlet(s)
USB port	Yes
USB port type	USB Type-B
RS-232 ports	1
Emergency Power Off (EPO) connector	Yes
Battery	
Battery replacement accessibility	Professional only
Battery technology	Sealed Lead Acid (VRLA)
Battery capacity	9 Ah
Battery voltage	12 V
Number of batteries supported	2
Typical backup time at full load	3 min
Typical backup time at half load	13.3 min
Battery recharge time	4 h
Charging current	1.5 A
Replacement battery cartridge	BPS24V40AC
Design	
Form factor	Tower
Product colour	Black
Housing material	Metal
Cable length	1.5 m
Display type	LCD
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 50 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 1500 m
Non-operating altitude	0 - 1500 m
Certificates	

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Compliance certificates	CE, EAC, UKCA, RoHS
Packaging content	
Cables included	USB cable
Manual	Yes
Weight & dimensions	
Width	86 mm
Depth	335 mm
Height	308 mm
Weight	10 kg
Packaging data	
Package weight	10.9 kg
Other features	
Bypass	GreenPower UPS

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903