

CyberPower OR600ERM1U uninterruptible power supply (UPS) Line-Interactive 0.6 kVA 360 W 6 AC outlet(s)

 Gamintojas: **CYBERPOWER** · Modelis: **OR600ERM1U** · EAN: **4712856274318** · Prekės kodas: **699356**


300,90 €

Kaina su PVM

 Be PVM: **248,68 €**

Sandėlyje


Prekė internetu

 Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Line-interactive UPS Topology
- ✓ Energy Saving Technology
- ✓ Simulated Sine Wave Output
- ✓ Automatic Voltage Regulation (AVR)
- ✓ Overload Protection
- ✓ Hot-swappable Batteries
- ✓ Surge and Spike Protection
- ✓ EMI and RFI Filtration
- ✓ Phone/Fax/Modem/DSL/Network Protection
- ✓ LCD Status Display



Aprašymas

CyberPower OR600ERM1U Line-Interactive UPS offers Simulated Sine Wave output power for office system devices including PCs, workstations, networking devices, and peripherals. It's typically integrated in the back office, server room, and data center environment to ensure a reliable backup power supply during power failures. In addition, the rackmount / tower convertible design gives it enhanced flexibility for installation and operation in almost any environment.

The UPS has a multifunction LCD display which offers real-time information, including input and output voltage levels, load and battery levels, battery runtime, overload warning, and a silent mode. With the network ports on the UPS, it prevents network devices from being subjected to sudden power surges caused by lightning, thereby avoiding potential system damage. As for battery maintenance, the UPS allows battery hot-

swapping, which enables users to perform normal battery maintenance without significant interruption.

Techninė specifikacija

Specifications	
Sandėlio grupė	USV & Stromversorgung [+611][-96]
Features	
UPS topology	Line-Interactive
Output power capacity	0.6 kVA
Output power	360 W
Waveform	Sine
Input operation voltage (min)	165 V
Input operation voltage (max)	271 V
Input frequency	50/60 Hz
Output operation voltage (min)	230 V
Output operation voltage (max)	230 V
Output frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	Yes
Maximum current	10 A
Surge energy rating	405 J
Response time	4 ms
Power factor	0.6
EMI/RFI noise filtering	Yes
Surge protection	Yes
Surge protection features	Digital Subscriber Line (DSL), Fax, Modem, Network, Telephone
Power protection features	Overload
Audible alarm(s)	Yes
Audible alarm modes	Low battery alarm, Overload alarm
Ports & interfaces	
AC outlet types	C13 coupler
Power plug	C14 coupler
AC outlets quantity	6 AC outlet(s)
USB port	Yes
Serial ports quantity	1
Modem (RJ-11) ports	1
Ethernet LAN (RJ-45) ports	1

Battery

Battery technology	Sealed Lead Acid (VRLA)
Number of batteries supported	1
Typical backup time at full load	4 min
Typical backup time at half load	13 min
Battery recharge time	8 h
Hot-swap battery	Yes

Design

Form factor	Rackmount
Product colour	Silver
Housing material	Metal
Rack capacity	1U
Cable length	1.83 m
Display type	LCD
LED indicators	Operation

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Certificates

Compliance certificates	RoHS
Certification	CE, EAC, RCM

Packaging content

Cables included	USB cable
-----------------	-----------

Weight & dimensions

Width	433 mm
Depth	235 mm
Height	44 mm
Weight	7.8 kg

Packaging data

Package width	530 mm
---------------	--------

Package depth	315 mm
Package height	155 mm
Package weight	10.3 kg
Logistics data	
Harmonized System (HS) code	8504408590
Country of origin	China
Matmenys ir svoris	
Matmenys (l × p × A)	15,00cm × 53,00cm × 29,00cm