

# XPG KYBER 850W Power Supply

Gamintojas: **ADATA** · Modelis: **75261263** · EAN: **4711085942470** · Prekės kodas: **700201**



## 94,90 €

Kaina su PVM

Be PVM: **78,43 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ 850 W 100 - 240 V 47 - 63 Hz
- ✓ Motherboard power connector: 24-pin ATX
- ✓ PC ATX 80 PLUS Gold
- ✓ Active 12 cm 2400 - 2400 RPM
- ✓ Black



## Aprašymas

### KYBER

#### Go for gold

XPG KYBER offers GOLD efficiency and adheres to Intel ATX 3.1 design guide specifications. With a 12V-2x6 connector available in the 750 and 850 watt models, it is an ideal PSU for most users.

#### Next-Gen Ready - ATX 3.1 COMPATIBLE

KYBER power supply units adhere to the Intel ATX 3.1 design guide specifications and offering a 12V-2x6 connector at 750 and 850 wattage category, KYBER can support the latest graphics cards, made specifically for those who require high graphic capability and performance.

#### Cybenetics LAMBDA / ETA Certified

XPG KYBER SERIES is certified by Cybenetics for its efficiency and noise level, scoring at the top of its category in both ETA and LAMBDA standards.

GOLD Certified Efficiency

KYBER series power supply units 80 PLUS GOLD certified, achieving up to 91.40% (115V) efficiency at 50% load.

Intelligent Fan-Curve Design

The intelligent fan-curve ensures quiet operation in a majority of user scenarios. By starting the fan control at a low RPM, achieving less noise and a much longer lifespan for both the fan and the overall PSU.

PEAK PERFORMANCE AND RELIABILITY

All XPG ATX 3.0 and ATX 3.1 power supplies are designed to support up to 235% power excursion, enabling the system to handle sudden power spikes, ensuring stability, and preventing crashes during intense workloads like gaming, rendering, and data processing.

Techninė specifikacija

| Specifications                                       |                                                            |
|------------------------------------------------------|------------------------------------------------------------|
| Sandėlio grupė                                       | PC Components Power Supplies PSUs above 800 Watts [+0][-0] |
| Power                                                |                                                            |
| Total power                                          | 850 W                                                      |
| AC input voltage                                     | 100 - 240 V                                                |
| AC input frequency                                   | 47 - 63 Hz                                                 |
| Power factor                                         | 0.99                                                       |
| Ports & interfaces                                   |                                                            |
| Motherboard power connector                          | 24-pin ATX                                                 |
| Peripheral (Molex) power connectors (4-pin)          | 2                                                          |
| Motherboard power cable length                       | 65 cm                                                      |
| Number of SATA power connectors                      | 6                                                          |
| SATA power cable length                              | 450 mm                                                     |
| EPS power connector (8-pin)                          | Yes                                                        |
| PCI Express power connectors (6+2 pin)               | 2                                                          |
| PCI Express power connectors (12+4 pin)              | 1                                                          |
| PCI Express power connectors (12+4 pin) cable length | 600 mm                                                     |
| ATX Power connector (24-pin)                         | Yes                                                        |
| Cabling type                                         | Non-Modular                                                |
| Performance                                          |                                                            |
| Purpose                                              | PC                                                         |
| Power supply unit (PSU) form factor                  | ATX                                                        |
| 80 PLUS certification                                | 80 PLUS Gold                                               |
| ATX version                                          | 3                                                          |
| Bearing technology                                   | FDB                                                        |

|                                   |                                                                        |
|-----------------------------------|------------------------------------------------------------------------|
| Mean time between failures (MTBF) | 100000 h                                                               |
| Design                            |                                                                        |
| Product colour                    | Black                                                                  |
| Cooling type                      | Active                                                                 |
| Fan diameter                      | 12 cm                                                                  |
| Number of fans                    | 1 fan(s)                                                               |
| Fan speed                         | 2400 - 2400 RPM                                                        |
| On/off switch                     | Yes                                                                    |
| Operational conditions            |                                                                        |
| Operating temperature (T-T)       | 0 - 40 °C                                                              |
| Certificates                      |                                                                        |
| Certification                     | CB/TUV/cTUVus/CE+UKCA/FCC+IC/LVD+UKCA/BSMI/RCM/BIS/EAC+ROHS/S-MARK/NOM |
| Weight & dimensions               |                                                                        |
| Width                             | 150 mm                                                                 |
| Depth                             | 140 mm                                                                 |
| Height                            | 86 mm                                                                  |
| Weight                            | 2.03 kg                                                                |
| Technical details                 |                                                                        |
| Sustainability compliance         | Yes                                                                    |
| Matmenys ir svoris                |                                                                        |
| Svoris                            | 2,56kg                                                                 |