Axagon EEM2-UG2 External USB-C 10Gbps metal box for M.2 NVMe SSD disks. Silver

Gamintojas: **AXAGON** · Modelis: **EEM2-UG2** · EAN: **8595247904287** · Prekės kodas: **701311**



24.90€

Kaina su PVM

Be PVM: **20.58€**

In Stock


Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ SSD enclosure NVMe-oF M.2
- ✓ Number of storage drives supported: 1
- ✓ NVMe
- ✓ USB connectivity
- ✓ S.M.A.R.T. support TRIM support UASP support
- ✓ 10 Gbit/s
- ✓ Power source type: USB
- ✓ Black, Grey










Aprašymas

Super fast external box AXAGON EEM2-UG2 is designed for NVMe (PCI-Express) M.2 SSD drives. It is equipped with a modern SuperSpeed USB-C connector for easy and reliable connection. Thank to PCI-Express and USB 3.2 Gen 2 interfaces up to 10Gb/s, you will enjoy the high speed of modern NVMe M.2 SSD drives. The external box supports TRIM function to reduce the gradual degradation of SSD performance over time. Booting from an SSD in an external box is also supported. In external box you can use M key and B&M key NVMe M.2 SSDs up to 22x80 mm without limiting the maximum capacity of the SSD. M.2 cards can be both single-sided or double-sided.

The box is equipped with a double-sided USB-C connector, which offers a convenient and fast connection without having to find the correct orientation of the cable. The USB-C connector also ensures reliable contact without the risk of accidental disconnection of the external drive. The included 22 cm connection cable is also equipped with a double-sided USB-C connector. It can be directly connected to both SuperSpeed + USB connectors on laptops and modern cell phones. A decently lit blue LED indicates that the computer is connected to the USB port with a permanent light and flashing when transferring the data. For efficient operation, the external box is programmed to suspend the drive after 5 minutes of inactivity.

The durable aluminium body of the box has very good contact with the M.2 disc due to the heat-conducting pads and the pressure mechanism. Effective heat dissipation into the metal body of the box significantly reduces the surface temperature of the disc and extends its life. Installation on supported operation systems is completely automatic. The external drive can be connected not only to computers and laptops, but also to cell phones and tablets if they have OTG support.

Super fast external box AXAGON EEM2-UG2 with USB 3.2 Gen 2 interface is designed for NVMe (PCI-Express) M.2 SSD disks.

Latest USB interface allows you to enjoy the speed of modern M.2 SSD drives. Due the fast USB 3.2 Gen 2 interface is the transmission Speed up to 10Gb/s. Convenient connection allows reversible USB-C connector. The external M.2 box also supports other modern functions, e.g. TRIM.

In the external box, NVMe M.2 SSD disks with a size up to 22x80 mm can be mounted. The box is not limited by capacity of SSD disks. M.2 cards may be one-sided or double-sided.

The aluminum body of the box and the heat-conductive pads ensure very good cooling of the inserted M.2 SSD.

Insert the M.2 SSD disk into this box and you can easily form a fast and compact external disk. The Box can be used with both computers and laptops, so with mobile phones and tablets with the OTG supporting function.

Input:
• USB 3.2 Gen 2 / SuperSpeed+ USB rate of up to 10 Gbit/s.
• Connection via reversible USB type C female connector.

Device support:
• NVMe M.2SSD disks,
• designed for M-key or B+M-key card formats,
• NGFF 75-pin M-key slot for NVMe M.2 drives.

Other features:
• Compatible with USB 3.2 Gen 2, backward compatible with USB 3.1 Gen 1 / USB 3.0. and USB 2.0.

• Supports transmission rates 10.000 / 5000 / 480 Mbit/s (SuperSpeed+ / SuperSpeed / HighSpeed).
• Support of M-key or B+M-key NVMe (PCI-Express) M.2 SSD disks without maximum capacity limitation.
• Support of M.2 drives with a size of 2242, 2260, 2280 mm.
• Support of both one-sided and double-sided M.2 SSDs.
• Compliant with PCI Express Base Specification Revision 3.1a
• Compliant with NVM Express 1.3 Specifikation.
• Compliant with USB Mass Storage Class Specifikation.
• The total bandwidth / transmission rate of the box is determined by the USB 3.2 Gen 2 interface used (theoretically up to 10 Gbit/s).
• The real bandwidth / transmission rate of the box is around 1000 MB/s (1 GB/s) is given by the limits of the USB 3.2 Gen 2 interface.
• Supports UASP (USB Attached SCSI) for faster data transmission in Windows 8 and later.
• Support of TRIM functionality to limit gradual degradation of the SSD performance over time.
• SSD boot support in external box.
• Possibility to connect your device while running thanks to the Hot Plug support.
• Full Plug and Play support.
• Standby Support - Drive asleep after 5 minutes of inactivity.
• Supplying the power via USB bus up to 900mA from one USB port is sufficient in all cases.
• A decent blue LED indicating the connection to the computer's USB port (permanent light) and data transmission (blinking).
• Heavy-duty aluminium body and the cooling pads helps to better cool the M.2 SSD.
• Higher surface temperature of the box is not a problem - thanks to the aluminum body, the heat generated by the operation of the disc is better dissipated and transferred to the surroundings.
• Connection via USB 3.2 Gen 2 Type-C female connector.
• USB Type-C male / USB Type-C male cable 22 cm long is included.

Other data:
• External box dimensions 115 x 39 x 11 mm.
• External box weight 43 g (without USB cable and M.2 SSD disk).

Supported operating systems:
• MS Windows 7 / 8 / 8.1 / 10 and later, Windows Server 2008 / 2012 / 2016 and later (all 32-bit and 64-bit Windows OS versions are supported), Mac OS X 10.x and higher, Linux with kernel 2.6.x and higher, Android (OS and device support required).
• Note: When operating under Windows 7, contact the manufacturer of the M.2 SSD to find whether this OS is supported.

Package contains:
• USB-C 3.2 Gen 2 external box for NVMe M.2 SSD,
• USB type C – type C cable 22 cm long,
• 3 thermally conductive pads,
• mounting material and a screwdriver,
• printed installation manual CZ / DE / DK / ENG / ESP / FIN / FR / GR / HR / HU / IT / NL / PL / PT / RO / RU / SK / SWE / BG / CN / TR / ARA,
• packed in a cardboard box with clearly indicated parameters.

Techninė specifikacija

Storage	
Storage drive size	M.2
Supported storage drive interfaces	NVMe-oF
Number of storage drives supported	1
Supported storage drive lengths	42,60,80 mm
NVMe	Yes

Ports & interfaces	
USB connectivity	Yes
USB version	3.2 Gen 2 (3.1 Gen 2)
USB connector type	USB Type-C
USB connector gender	Female
USB ports quantity	1
Design	
Product type	SSD enclosure
Product colour	Black, Grey
Material	Aluminium
LED indicators	Yes
Certification	CE, RoHS
Performance	
Data transfer rate	10 Gbit/s
UASP support	Yes
TRIM support	Yes
S.M.A.R.T. support	Yes
Plug and Play	Yes
Power	
Power source type	USB
External power adapter	No
System requirements	
Mobile operating systems supported	Yes
Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows 8.1
Linux operating systems supported	Yes
Mac operating systems supported	Yes
Weight & dimensions	
Width	115 mm
Depth	39 mm
Height	11 mm
Weight	43 g
Cable length	0.22 m
Package width	83 mm
Package depth	177 mm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Package height	28 mm
Package weight	103 g
Packaging content	
Package type	Box
AC adapter included	No
Cables included	USB Type-C to USB Type-C
Screws included	Yes
Screwdriver included	Yes
Manual	Yes
Technical details	
Warranty period	2 year(s)
Compliance certificates	RoHS
Matmenys ir svoris	
Matmenys (I × P × A)	3.00cm × 9.00cm × 18.00cm
Svoris	0.06kg

Dokumentai ir vaizdo įrašai

› User manual

Gamintojo ir saugos informacija

MANUFACTURER

RealQ, s.r.o.
Železná 663/5, 619 00 Brno-jih, CZ
axagon.eu

DISTRIBUTOR

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt