

EIZO ColorEdge CS2731 computer monitor 68.6 cm (27") 2560 x 1440 pixels Quad HD LCD Black

 Gamintojas: **EIZO** · Modelis: **CS2731-BK** · EAN: **4995047054580** · Prekės kodas: **701360**


1 022,90 €

Kaina su PVM

 Be PVM: **845,37 €**

Sandėlyje


Prekė internetu

 Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 27-inch wide gamut LCD with 2560 x 1440 pixels (WQHD) to deliver ultra-sharp details
- ✓ EIZO microchip ensures precise, consistent and lasting colour display
- ✓ Wide gamut covering 99% of the Adobe RGB colour gamut
- ✓ Precise hardware calibration of brightness, white balance and gamma
- ✓ Digital Uniformity Equaliser for top-rate luminance distribution and colour purity
- ✓ Colour precision ensured via 16-bit look-up-table and up to 10-bit colour reproduction
- ✓ USB-C (DisplayPort signal channel and power supply up to 60 W), DisplayPort, DVI-D and HDMI ports
- ✓ USB hub with two USB 3.1 and two USB 2.0 downstream ports
- ✓ ColorNavigator calibration software available for free download
- ✓ Recommended optional accessories: measuring device for hardware calibration and monitor hood



Aprašymas

The CS2731 unites precision, colour fidelity and cutting-edge connectivity thanks to its USB-C port. This makes the monitor the central interface for the graphic workflow of sophisticated creatives with high standards. The wide gamut, 16-bit look-up-table and precise factory calibration of the CS2731 allows you to enjoy an unadulterated look at your image files in creative workflows requiring high colour accuracy. Convenient functionalities such as monitor signal transmission, rapid data transfer and the power supply feature for connected devices are enabled with just one

USB-C port.

Techninė specifikacija

Specifications	
Sandėlio grupė	Root/Electronics/PC peripherals/Monitors [+94][-352]
Display	
Display diagonal	68.6 cm (27")
Display resolution	2560 x 1440 pixels
Native aspect ratio	16:9
Display technology	LCD
Touchscreen	No
HD type	Quad HD
Panel type	IPS
Response time	16 ms
Screen shape	Flat
Contrast ratio (typical)	1000:1
Maximum refresh rate	60 Hz
Display number of colours	1.073 billion colours
LED backlight	Yes
Backlight type	W-LED
Display brightness (typical)	350 cd/m²
Anti-glare screen	Yes
Supported graphics resolutions	2560 x 1440, 1920 x 1200 (WUXGA)
Supported video modes	1080p, 1080i, 720p, 576p, 576i, 480p, 480i
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.233 x 0.233 mm
Pixel density	109 ppi
Viewable size, horizontal	59.7 cm
Viewable size, vertical	33.6 cm
Digital horizontal frequency	15 - 89 kHz
Digital vertical frequency	23 - 61 Hz
Colour depth	10 bit
Colour gamut standard	Adobe RGB, DCI-P3, sRGB
sRGB coverage (typical)	100%

Adobe RGB coverage	99%
DCI-P3 coverage	95%
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Flicker-free technology	Yes
Multimedia	
Built-in speaker(s)	No
Built-in camera	No
Design	
Market positioning	Photo editing
Product colour	Black
Feet colour	Black
Ports & interfaces	
Built-in USB hub	Yes
HDMI	Yes
USB hub version	2.0 / 3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-B, USB Type-C
Number of upstream ports	2
Number of USB Type-B upstream ports quantity	1
Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	4
USB Type-C DisplayPort Alternate Mode	Yes
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	60 W
VGA (D-Sub) ports quantity	0
DVI port	Yes
DVI-D ports quantity	1
HDMI ports quantity	1
DisplayPorts quantity	1
Built-in KVM switch	Yes
HDCP	Yes
Ergonomics	
VESA mounting	Yes

Cable lock slot	Yes
Height adjustment	Yes
Panel mounting interface	100 x 100 mm
Cable lock slot type	Kensington
Adjustable height (max)	15.5 cm
Pivot	Yes
Pivot angle	-90 - 90°
Swivelling	Yes
Swivel angle range	0 - 344°
Tilt adjustment	Yes
Tilt angle range	-5 - 35°
On Screen Display (OSD)	Yes
Power	
Energy efficiency class (SDR)	G
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	35.7 kWh
Power consumption (typical)	35.7 W
Power consumption (standby)	0.5 W
Power consumption (max)	159 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	0 - 35 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width (with stand)	638 mm
Depth (with stand)	265 mm
Height (with stand)	404.1 mm
Weight (with stand)	10.1 kg
Width (without stand)	638 mm
Depth (without stand)	75 mm

Height (without stand)	378.2 mm
Weight (without stand)	6.5 kg
Packaging content	
Stand included	Yes
Cables included	AC, HDMI, USB Type-C to USB Type-C
Quick start guide	Yes
Other features	
Hardware calibration	Yes
Warranty period	5 year(s)
Look-up table (LUT) bit depth	16
Compliance certificates	RoHS
Certification	CE, CB, TÜV/GS, TÜV/Ergonomics (including ISO 9241- 307), cTÜVus, TÜV/S, EAC, PSE, FCC-B, CAN ICES-3 (B), RCM, VCCI-B, CCC, RoHS, China RoHS, WEEE
Logistics data	
Harmonized System (HS) code	85285210
Matmenys ir svoris	
Matmenys (I × P × A)	73,00cm × 55,00cm × 34,00cm