

Eaton 5E Gen2 700 uninterruptible power supply (UPS) Line-Interactive 0.7 kVA 360 W 4 AC outlet(s)

Gamintojas: **EATON** · Modelis: **5E700I** · EAN: **3553340704130** · Prekės kodas: **701463**



91,90 €

Kaina su PVM

Be PVM: **75,95 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Line-Interactive
- ✓ 0.7 kVA 360 W
- ✓ 4 AC outlet(s)
- ✓ Tower Black



Aprašymas

Eaton 5E Gen2 delivers efficient, affordable power protection for critical applications in both residential and professional settings.

Power protection

Eaton 5E Gen2 UPS protects application and data against power loss.

Double-boost Automatic Voltage Regulation (AVR) technology regulates grid fluctuations (under and overvoltage) to save battery power in the event of power outage.

A wide product range covers the power requirements of many IT devices.

Auto-restart function enables the UPS to restart automatically when mains power recovers after a total battery discharge.

Easy integration

Eaton 5E Gen2 implements national outlet formats (FR, DIN/IT, BS and IEC) to make application connection and protection easy.

Fanless design up to 1200VA ensures silent operation in residential settings.

Compact housing makes it easy to integrate in home or office.

Easily manage your UPS from your PC (on USB models):

Integrates automatically with Windows / MacOS / Linux power management for safe system shutdown.

Analyse energy usage and manage UPS parameters with Eaton UPS Companion software.

Peace of mind

A leading manufacturer you can trust with decades of experience and high quality standards: CE-ertified by an external agency (TUV) according to latest international safety standards.

Know you can depend on batteries round the clock:

5E Gen2 batteries are permanently recharged (even when off).

UPS can start without mains (cold start).

Automatic battery test and battery replacement alarm.

Ensure peace of mind thanks to a two-year warranty.

Techninė specifikacija

Specifications	
Sandėlio grupė	Root/Accessories Exploitation/Power supply/UPSs and power strips/UPSs [+51][-349]
Features	
UPS topology	Line-Interactive
Output power capacity	0.7 kVA
Output power	360 W
Input operation voltage (min)	220 V
Input operation voltage (max)	240 V
Input frequency	50/60 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Noise level	25 dB
Power protection features	Over voltage, Under voltage
Audible alarm(s)	Yes
Audible alarm modes	Battery replacement
Auto-restart	Yes
Power source type	AC
Ports & interfaces	
AC outlet types	C13 coupler
AC outlets quantity	4 AC outlet(s)
Battery	
Automatic battery test	Yes
Cold start	Yes

Design

Form factor	Tower
Product colour	Black
Control type	Buttons

Operational conditions

Operating temperature (T-T)	0 - 40 °C
-----------------------------	-----------

Certificates

Compliance certificates	Low Voltage Directive (LVD), RoHS, WEEE
Certification	EN IEC 62040-1:2019; EN 62040-2:2006; IEC 62040-2: 2016, IEC 62040-3: 2021; CE; EAC; UKCA; Cm; Ukr

Weight & dimensions

Width	100 mm
Depth	288 mm
Height	148 mm
Weight	4.3 kg

Sustainability

Sustainability compliance	Yes
---------------------------	-----

Matmenys ir svoris

Matmenys (I × P × A)	23,00cm × 36,00cm × 19,00cm
----------------------	-----------------------------