



TP-LINK 16-Port Gigabit Easy Smart Switch 16 Gigabit RJ45 Ports MTU/Port/Tag- based VLAN QoS IGMP Snooping

Modelis: TL-SG116E

Gamintojas: TP-LINK

EAN: 6935364084301

Prekės kodas: 70147

72.99€

The TL-SG116E Unmanaged Pro switch is an ideal upgrade on unmanaged switches, suited for home and small business networks. A plug-and-play design makes for easy deployment without the need for a technician, while a robust metal casing provides better protection for components. Equipped with intelligent management features like QoS, VLAN, IGMP Snooping and more, this switch is effective in both simple and more demanding network environments.

TL-SG116E excels not only in simple plug-and-play networks but also in more demanding environments. Network monitoring enables users to observe traffic behavior. Port Mirroring, Loop

Prevention and Cable Diagnostics allow connection problems on your network to be identified and

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

located. Administrators can designate the priority of traffic based on Port/802.1p/DSCP QoS, for example, to ensure that voice and video applications remain clear and lag-free. Combining security with network performance, TL-SG116E supports MTU VLAN, port-based VLAN and 802.1Q-based VLAN functions.

Product Description: TP-Link TL-SG116E Unmanaged Pro - switch - 16 ports - unmanaged | Device Type: Switch - 16 ports - unmanaged | Subtype: Gigabit Ethernet | Ports: 16 x 10/100/1000 | Performance: Packet forwarding rate: 23.81 Mpps Switching capacity: 32 Gbps | Capacity: VLAN IDs: 4000 VLANs supported: 32 | MAC Address Table Size: 8K entries | Jumbo Frame Support: 9KB | Features: Auto-negotiation, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, port mirroring, store and forward, Cable Diagnostics Function, fanless, loop prevention, Storm Control, rate limit, Static Link Aggregation | Compliant Standards: IEEE 802.3u, IEEE 802.3i, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x | Dimensions (WxDxH): 28.6 cm x 11.17 cm x 2.54 cm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903