

TP-Link Festa F61 1800 Mbit/s White Power over Ethernet (PoE)

Gamintojas: **TP-LINK** · Modelis: **FESTA F61** · EAN: **8885021370194** · Prekės kodas: **701578**



157,91 €

Kaina su PVM

Be PVM: **130,50 €**

Sandėlyje



Prekę internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Up to 1.8 Gbps WiFi 6 Speeds: 574 Mbps on 2.4 GHz and 1201 Mbps on 5 GHz*
- ✓ Free cloud centralized management via the Festa app or the web†
- ✓ Mesh & Seamless Roaming enable smooth wireless connectivity
- ✓ 1x Gigabit Port for high-speed transmissions
- ✓ Supports both 802.3at PoE and Passive PoE (PoE adapter included) for easy installation
- ✓ Smart antennas and high-power amplifiers provide robust full coverage
- ✓ IP67-Rated enclosure withstands harsh weather
- ✓ Easy setup and use, no professional technician required. Self-Organizing Networking and Zero-Touch Provisioning technology make it a breeze



Aprašymas

Festa □ A Networking Solution Built For Small Business, No IT Required

Festa offers business-class features with consumer-inspired simplicity. Our free cloud-based centralized management is accessible via the Festa app or web, providing essential features for small businesses without the complexity required by larger-scale operations.

Techninė specifikacija

Specifications

Sandėlio grupė	Server/Storage/Network > Access Points/Routers [+1129][-325]
----------------	--

Features

2.4 GHz	Yes
5 GHz	Yes
6 GHz	No
Maximum data transfer rate	1800 Mbit/s
Maximum data transfer rate (2.4 GHz)	574 Mbit/s
Maximum data transfer rate (5 GHz)	1201 Mbit/s
Ethernet LAN data rates	1000 Mbit/s
Networking standards	IEEE 802.11n, IEEE 802.11a, IEEE 802.11ac, IEEE 802.3af, IEEE 802.11b, IEEE 802.11g
Number of users	250 user(s)
MIMO	Yes
MIMO type	Multi User MIMO
Spread spectrum method	OFDMA
VLAN support	Yes
Wireless isolation	Yes
Airtime Fairness (ATF)	Yes
Quality of Service (QoS) support	Yes
BeamForming	Yes
Transmitting power (CE)	20 - 28 dBm
Transmitting power (FCC)	25 - 25 dBm

Security

Security algorithms	WPA2-Enterprise, WPA2-Personal, WPA-Enterprise, SNMPv2, SNMPv3, WPA-Personal, SSH, WPA3-Enterprise, WPA3-Personal
MAC address filtering	Yes
Service Set Identifier (SSID) features	Multiple SSIDs, SSID broadcast
Number of SSID supported	16
Guest access	Yes
Remote Authentication Dial-In User Service (RADIUS)	Yes

Management features

Web-based management	Yes
Syslog	Yes
Firmware upgradeable	Yes

Ports & interfaces

Ethernet LAN (RJ-45) ports	1
USB 2.0 ports quantity	0
Power	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) type supported	Active PoE, Passive PoE
Power consumption (max)	14.7 W
Design	
Placement	Pole, Wall
Product colour	White
International Protection (IP) code	IP67
Reset button	Yes
LED indicators	Yes
Antenna	
Antenna type	Internal
Antenna direction type	Omni-directional
Antenna features	Detachable antenna
Antennas quantity	2
Antenna gain level (max)	5 dBi
Certificates	
Compliance certificates	Federal Communications Commission (FCC), RoHS, CE
Weight & dimensions	
Width	280.4 mm
Depth	106.5 mm
Height	63.5 mm
Weight	780 g
Packaging content	
Quantity per pack	1 pc(s)
PoE adapter included	Yes
Cables included	Power
Mounting kit	Yes
Quick start guide	Yes
Operational conditions	
Operating relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	-30 - 70 °C

Storage temperature (T-T)	-40 - 70 °C
---------------------------	-------------

Storage relative humidity (H-H)	5 - 90%
---------------------------------	---------

Matmenys ir svoris

Matmenys (I × P × A)	16,00cm × 16,00cm × 4,00cm
----------------------	----------------------------