

NET CAMERA 5MP IR DOME/HDBW5541R-ASE-0280BOPAT DAHUA

Gamintojas: **DAHUA** · Modelis: **HDBW5541R-ASE-0280BOPAT** · EAN: **6923172527431** · Prekės kodas: **701747**



142,90 €

Kaina su PVM

Be PVM: **118,10 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 1/2.7" 5Megapixel progressive scan CMOS
- ✓ H.265 & H.264 triple-stream encoding
- ✓ 20 fps@2592 × 1944, 50/60 fps@1080P (1920 × 1080)
- ✓ WDR (120 dB), Day/Night (ICR), 3D DNR, AWB, AGC, BLC
- ✓ Multiple network monitoring: Web viewer, CMS (DSS/PSS) & DMSS
- ✓ 2.8 mm fixed lens (3.6 mm, 6.0 mm optional)
- ✓ 1/1 Alarm in/out, 1/1 audio in/out
- ✓ Max. IR LEDs Length 50 m
- ✓ Micro SD memory, IP67, IK10

Aprašymas

- 1/2.7" 5Megapixel progressive scan CMOS
- H.265 & H.264 triple-stream encoding
- 20 fps@2592 × 1944, 50/60 fps@1080P (1920 × 1080)
- WDR (120 dB), Day/Night (ICR), 3D DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS (DSS/PSS) & DMSS
- 2.8 mm fixed lens (3.6 mm, 6.0 mm optional)
- 1/1 Alarm in/out, 1/1 audio in/out
- Max. IR LEDs Length 50 m
- Micro SD memory, IP67, IK10

Summary: Dahua Technology Pro HDBW5541R-ASE. Type: IP security camera, Placement supported: Indoor & outdoor, Connectivity technology: Wired. Mounting type: Ceiling/wall, Product colour: White, Form factor: Dome. Minimum illumination: 0.002 lx, Angle of rotation: 355°, Lens viewing angle, horizontal: 98°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm (1 / 2.7"), Number of effective pixels (H x V): 2688 x 1520 pixels. Detect distance: 30 m, Normal focusing range: 2.5 - 6 m, Fixed focal length: 2.8 mm | Vendor Homepage: <https://www.dahuasecurity.com/products/productDetail/32847> | Form factor: Dome | Mounting type: Ceiling/wall | Product colour: White | Housing material: Metal | International Protection (IP) code: IP67 | IK code: IK10 | Fog proof: Yes | Type: IP security camera | Connectivity technology: Wired | Placement supported: Indoor & outdoor | People counting function: Yes | Alarm input/output: Yes | Plug and Play: Yes | Camera pan control: Yes |

Camera tilt control: Yes | Minimum illumination: 0.002 | Angle of rotation: 355 | Lens viewing angle, horizontal: 98 | Lens viewing angle, vertical: 71 | Lens viewing angle, diagonal: 129 | Tilt angle range: 0 - 65 | Pan range: 0 - 355 | Auto flip: Yes | White balance: Auto/Lamp/Manual/Natural/Outdoor | Camera shutter type: Electronic | Camera shutter speed: 1/3 - 1/100000 | Adjustment shutter speed: Auto/Manual | Number of sensors: 1 | Optical sensor size: 1/2.7 | Progressive scan: Yes | Number of effective pixels (H x V): 2688 x 1520 | Sensor type: CMOS | Number of lenses: 1 | Detect distance: 30 | Auto focus: Yes | Fixed focus: Yes | Maximum aperture number: 1.6 | Fixed focal length: 2.8 | Normal focusing range: 2.5 - 6 | Night vision: Yes | Night vision distance: 80 | LED type: IR | Number of illumination LEDs: 3 | Maximum resolution: 2688 x 1520 | Total megapixels: 5 | Video compression formats: H.264/H.264+/H.265/H.265 Pro/H.265 Pro+/H.265+ | Supported graphics resolutions: 1280 x 720 (HD 720)/1280 x 960/1920 x 1080 (HD 1080)/2304 x 1296/2560 x 1440/2688 x 1520/352 x 240/352 x 288/640 x 480 (VGA)/704 x 576 | Supported video modes: 1080p/720p | Frame rate: 30 | Video intelligence analytic: Yes | Video streaming: Yes | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Gain control type: Auto/Manual | Back Light Compensation (BLC): Yes | Bit rate: H.264: 32 Kbps-8192 Kbps, H.265: 19 Kbps- 8192 Kbps | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Digital Wide Dynamic Range (DWDR): Yes | Flip & mirror: Yes | Highlight Compensation (HLC): Yes | Privacy masking: Yes | Region of Interest (ROI) encoding: Yes | Smart IR: Yes | Audio input channels: 1.0 | Audio output channels: 1.0 | Audio formats supported: AAC | Voice codecs: G.711a/G.711alaw/G.723/G.723.1/G.726/G.726-32 | Ethernet LAN: Yes | Ethernet interface type: Fast Ethernet | Networking standards: IEEE 802.1x | Supported network protocols: IPv4;IPv6;HTTP;HTTPS;TCP;UDP;ARP;RTP;RTSP;RTCP ;RTMP;SMTP;FTP;SFTP;DHCP;DNS;DDNS;QoS;UPnP ;NTP;Multicast;ICMP;IGMP;NFS;PPPoE;SNMP | Wi-Fi: No | Bluetooth: No | Number of users: 20 | Quality of Service (QoS) support: Yes | Streaming method: Multicast/Unicast | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 256 | Ethernet LAN (RJ-45) ports: 1 | DC-in jack: Yes | Active tampering alarm: Yes | Mirror: Yes | Motion sensor: Yes | Privacy protection: Yes | Video motion detection: Yes | Web-based management: Yes | Web browser: Yes | Management software: Smart PSS, DSS, DMSS | Power source type: AC,DC,PoE | AC input voltage: 24 | Power consumption (typical): 12.4 | DC output voltage: 12 | Operating temperature (T-T): -30 - 60 | Storage temperature (T-T): -30 - 60 | Operating relative humidity (H-H): 0 - 95 | Windows operating systems supported: Yes | Mobile operating systems supported: Android/iOS | Depth: 159 | Height: 117.9 | Weight: 950 | Number of cameras: 1 | Manual: Yes | Unit Calculated Weight: 0.665 | Product Net Weight: 0.46 | Unit Calculated Volume: 0.004167 | Units per Shipping Box: 20 | Unit Width: 13.5 | Units per Pallet: 0 | Shipping Box Height: 31.1 | Unit Depth: 15.5 | Unit Height: 15.5 | Name: NET CAMERA 5MP IR DOME/HDBW5541R-ASE-0280BOPAT DAHUA | Model: IPC-HDBW5541R-ASE-OPAT

Techninė specifikacija

Specifications

Sandėlio grupė

Network Cameras [+147][(-359)]

Matmenys ir svoris

Matmenys (I × P × A)

16,00cm × 14,00cm × 16,00cm