

iiyama ProLite T1931SR-B2S kompiuterio monitorius 48,3 cm (19") 1280 x 1024 pikseliai SXGA LCD Lietimui jautrus ekranas Ant stalo Juoda

Gamintojas: **IIYAMA** · Modelis: **T1931SR-B2S** · EAN: **4948570127757** · Prekės kodas: **702293**



465,90 €

Kaina su PVM

Be PVM: **385,04 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 48,3 cm (19") Juoda
- ✓ Įmontuoti garsiakalbiai
- ✓ HDMI „DisplayPort“ kiekis: 1
- ✓ Ekranas: Plokščias
- ✓ Reakcijos laikas: 14 ms Atsako trukmės matavimo tipas: GTG (Gray to Gray)
- ✓ 1280 x 1024 pikseliai SXGA Skydo tipas: IPS
- ✓ Energijos vartojimo efektyvumo klasė (SDR): E ErP CE, cULus, EAC, REACH, RoHS, UKCA, VCCI, WEEE





Aprašymas

The ProLite T1931SR-B2S is designed for workplaces where touch interaction needs to be simple, reliable and practical. Its 5-wire resistive touch technology responds to almost any suitable input method, including a finger, glove, stylus or pen-like tool. This makes it ideal for environments where users work quickly, wear gloves or need dependable touch operation without relying on bare fingers. With its IP54-rated front surface, the display is protected against dust and splashing water from the front, making it a strong choice for retail counters, restaurants, workshops, warehouses and light industrial applications. The monitor also offers flexible analogue and digital inputs with USB touch support for easy integration. An adjustable ergonomic stand and integrated cable management help create a clean, comfortable and professional workspace.

Techninė specifikacija

Display	
Display diagonal	48.3 cm (19")
Display resolution	1280 x 1024 pixels
Native aspect ratio	5:4
Display technology	LCD
Touchscreen	Yes
HD type	SXGA
Panel type	IPS
Response time	14 ms
Screen shape	Flat
Contrast ratio (typical)	1000:1
Display number of colours	16.7 million colours
Touchscreen type	Table
Touchscreen technology	Resistive
Touch technology	Single-touch
Number of simultaneous touchpoints	1
Display brightness (peak)	250 cd/m²
Display brightness (typical)	195 cd/m²
Display brightness	195 cd/m²
Response time measurement type	GTG (Gray to Gray)
Anti-glare screen	Yes
Viewing angle, horizontal	178°

Viewing angle, vertical	178°
Pixel pitch	0.293 x 0.293 mm
Horizontal scan range	31.5 - 80 kHz
Viewable size, horizontal	37.5 cm
Viewable size, vertical	30 cm
Display diagonal (metric)	48 cm
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Multimedia	
Built-in speaker(s)	Yes
Built-in camera	No
Number of speakers	2
RMS rated power	2 W
Design	
Market positioning	Business
Product colour	Black
Front bezel colour	Black
Ports & interfaces	
Built-in USB hub	No
HDMI	Yes
Headphone out	No
USB Touch port	Yes
VGA (D-Sub) ports quantity	1
DisplayPorts quantity	1
Audio input	Yes
HDCP	Yes
Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Height adjustment	No
Panel mounting interface	100 x 100 mm
Cable management	Yes
Cable lock slot type	Kensington


Tilt adjustment	Yes
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Traditional Chinese, German, English, Spanish, French, Italian, Japanese
Power	
Energy efficiency class (SDR)	E
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	13 kWh
Power consumption (typical)	20 W
Power consumption (standby)	1.5 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Weight & dimensions	
Width (with stand)	432 mm
Depth (with stand)	240 mm
Height (with stand)	432 mm
Weight (with stand)	6 kg
Packaging data	
Package width	530 mm
Package depth	190 mm
Package height	495 mm
Package weight	8 kg
USB cable length	1.8 m
Packaging content	
Cables included	AC, USB, HDMI, DisplayPort, Audio
Quick start guide	Yes
Audio cable length	1.8 m
DisplayPort cable length	1.8 m
HDMI cable length	1.8 m
Power cable length	1.8 m
Sustainability	
Sustainability certificates	ErP
Other features	

International Protection (IP) code	IP54
Compatible operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
Brightness	195 cd/m²
Packaging content	Screwdriver
Active display area (W x H)	374.8 x 299.8 mm
Weight	6 kg
Height	432 mm
Width	432 mm
Depth	240 mm
Compliance certificates	CE, cULus, EAC, REACH, RoHS, UKCA, VCCI, WEEE
Mean time between failures (MTBF)	50000 h
User controls	contrast, brightness, lock mode (power, OSD), auto adjust, OSD, H. position, V. position, H-size, fine, OSD H. position, OSD V. position, OSD timeout, reset, input select, OSD language, colour temperature, volume, mute
Touch method	stylus, finger, glove, glove (latex)
Control panel	Menu, Scroll up/ Brightness, Scroll down/ Mute, Select, Power

Matmenys ir svoris

Matmenys (I x P x A)	53,00cm x 49,00cm x 19,00cm
Svoris	7,64kg

Energijos efektyvumas ir ekologinis projektavimas



Energijos efektyvumo klasė

E A-G

- > [Energijos etiketė](#)
- > [Gaminio informacijos lapas](#)
- > [EPREL duomenų bazė](#)



1000/1000

Dokumentai ir vaizdo įrašai

- › Naudojimo instrukcija
- › Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

iiyama International

Wijkmeerstraat 8, 2131 HA Hoofddorp, NL

[iiyama.com](https://www.iiyama.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt