

# iiyama ProLite TF1615MC-B1 computer monitor 39.6 cm (15.6") 1920 x 1080 pixels Full HD Touchscreen Black

Gamintojas: **IIYAMA** · Modelis: **TF1615MC-B1** · EAN: **4948570121793** · Prekės kodas: **703468**



## 476,90 €

Kaina su PVM

Be PVM: **394,13 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ 39.6 cm (15.6") Black
- ✓ HDMI DisplayPorts quantity: 1
- ✓ Screen shape: Flat
- ✓ Response time: 25 ms
- ✓ 1920 x 1080 pixels Full HD Panel type: IPS
- ✓ Energy efficiency class (SDR): E ErP CE, cULus, EAC, REACH, RoHS, UKCA, WEEE



## Aprašymas

The ProLite TF1615MC-B1 (15.6 inch) uses PCAP touch technology and is built into an eye-catching bezel with edge-to-edge glass. Thanks to a glass overlay covering the screen and a rugged bezel, it guarantees high durability and scratch-resistance, making it perfect for kiosk and high use public facing applications. Equipped with a foam seal finish it supports seamless integration into kiosks and provides IP65 rating resulting in dust and water resistance from the front. Landscape, portrait and face-up orientation ensures flexible mounting possibilities in almost any installation. For ease of integration, the ProLite TF1615MC-B1 can be equipped with optional external mounting brackets (OMK5-1) making it an ideal solution for kiosk integrators, industrial environments, control rooms and interactive multimedia.

## Techninė specifikacija

| Specifications                     |                                                     |
|------------------------------------|-----------------------------------------------------|
| Sandėlio grupė                     | > Monitore > Monitore (TFT, LCD, LED) [+1779][-139] |
| Display                            |                                                     |
| Display diagonal                   | 39.6 cm (15.6")                                     |
| Display resolution                 | 1920 x 1080 pixels                                  |
| Native aspect ratio                | 16:9                                                |
| Touchscreen                        | Yes                                                 |
| HD type                            | Full HD                                             |
| Panel type                         | IPS                                                 |
| Response time                      | 25 ms                                               |
| Screen shape                       | Flat                                                |
| Contrast ratio (typical)           | 1000:1                                              |
| Touchscreen technology             | Projected capacitive system                         |
| Number of simultaneous touchpoints | 10                                                  |
| Display brightness (peak)          | 450 cd/m²                                           |
| Display brightness (typical)       | 450 cd/m²                                           |
| Display brightness                 | 405 cd/m²                                           |
| Aspect ratio                       | 16:9                                                |
| Viewing angle, horizontal          | 178°                                                |
| Viewing angle, vertical            | 178°                                                |
| Pixel pitch                        | 0.17925 x 0.17925 mm                                |
| Horizontal scan range              | 31.5 - 67.5 kHz                                     |
| Viewable size, horizontal          | 34.5 cm                                             |
| Viewable size, vertical            | 19.5 cm                                             |
| Display diagonal (metric)          | 39.5 cm                                             |
| Surface hardness                   | 7H                                                  |
| Design                             |                                                     |
| Market positioning                 | Business                                            |
| Product colour                     | Black                                               |
| Front bezel colour                 | Black                                               |
| Glass thickness                    | 3.3 mm                                              |
| Ports & interfaces                 |                                                     |
| Built-in USB hub                   | Yes                                                 |
| HDMI                               | Yes                                                 |

|                                         |                                                                          |
|-----------------------------------------|--------------------------------------------------------------------------|
| Headphone out                           | Yes                                                                      |
| USB Touch port                          | Yes                                                                      |
| VGA (D-Sub) ports quantity              | 1                                                                        |
| DisplayPorts quantity                   | 1                                                                        |
| HDCP                                    | Yes                                                                      |
| <b>Ergonomics</b>                       |                                                                          |
| VESA mounting                           | Yes                                                                      |
| Panel mounting interface                | 100 x 100 mm                                                             |
| On Screen Display (OSD)                 | Yes                                                                      |
| On Screen Display (OSD) languages       | Traditional Chinese, German, English, Spanish, French, Italian, Japanese |
| <b>Power</b>                            |                                                                          |
| Energy efficiency class (SDR)           | E                                                                        |
| Energy efficiency class (HDR)           | Not available                                                            |
| Energy consumption (SDR) per 1000 hours | 11 kWh                                                                   |
| Power consumption (typical)             | 18 W                                                                     |
| Power consumption (standby)             | 1.5 W                                                                    |
| Power consumption (off)                 | 0.3 W                                                                    |
| AC adapter output voltage               | 12 V                                                                     |
| Power supply type                       | External                                                                 |
| Energy efficiency scale                 | A to G                                                                   |
| <b>Operational conditions</b>           |                                                                          |
| Operating temperature (T-T)             | 0 - 40 °C                                                                |
| Storage temperature (T-T)               | -20 - 60 °C                                                              |
| <b>Weight &amp; dimensions</b>          |                                                                          |
| Width (with stand)                      | 398.5 mm                                                                 |
| Depth (with stand)                      | 42 mm                                                                    |
| Height (with stand)                     | 246 mm                                                                   |
| Weight (with stand)                     | 2.5 kg                                                                   |
| Width (without stand)                   | 398.5 mm                                                                 |
| Depth (without stand)                   | 42 mm                                                                    |
| Height (without stand)                  | 246 mm                                                                   |
| Weight (without stand)                  | 2.5 kg                                                                   |
| <b>Packaging data</b>                   |                                                                          |
| Package width                           | 470 mm                                                                   |

|                |        |
|----------------|--------|
| Package depth  | 343 mm |
| Package height | 145 mm |
| Package weight | 4.3 kg |
| Package type   | Box    |

#### Packaging content

|                        |                            |
|------------------------|----------------------------|
| Cables included        | AC, USB, HDMI, DisplayPort |
| Power adapter included | Yes                        |
| Quick start guide      | Yes                        |

#### Sustainability

|                             |     |
|-----------------------------|-----|
| Sustainability certificates | ErP |
|-----------------------------|-----|

#### Other features

|                                    |                                                                                                                                                                                                                                                                                    |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| International Protection (IP) code | IP65                                                                                                                                                                                                                                                                               |
| Compatible operating systems       | All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.                                                            |
| AC adapter included                | Yes                                                                                                                                                                                                                                                                                |
| Brightness                         | 405 cd/m²                                                                                                                                                                                                                                                                          |
| Packaging content                  | AC adapter, external control pad                                                                                                                                                                                                                                                   |
| Active display area (W x H)        | 345.2 x 194.6 mm                                                                                                                                                                                                                                                                   |
| Weight                             | 2.5 kg                                                                                                                                                                                                                                                                             |
| Height                             | 246 mm                                                                                                                                                                                                                                                                             |
| Width                              | 398.5 mm                                                                                                                                                                                                                                                                           |
| Depth                              | 42 mm                                                                                                                                                                                                                                                                              |
| Compliance certificates            | CE, cULus, EAC, REACH, RoHS, UKCA, WEEE                                                                                                                                                                                                                                            |
| Mean time between failures (MTBF)  | 50000 h                                                                                                                                                                                                                                                                            |
| Certification                      | CE, EAC, RoHS support, ErP, WEEE, cULus, REACH, UKCA                                                                                                                                                                                                                               |
| User controls                      | picture (contrast, brightness, H.position, V.position, H.size, phase, clock, auto adjust), advanced (colour temperature, sharpness), OSD (OSD timeout, OSD position, OSD H.position, OSD V.position, touch switch), option (reset, language, source select, display mode, factory) |
| Touch method                       | stylus, finger, glove (latex)                                                                                                                                                                                                                                                      |
| Control panel                      | menu,scroll up/ brightness, scroll down/ contrast, select, power                                                                                                                                                                                                                   |

#### Matmenys ir svoris

|                      |                             |
|----------------------|-----------------------------|
| Matmenys (I × P × A) | 48,00cm × 35,00cm × 15,00cm |
| Svoris               | 4,21kg                      |