

Hannspree HT279PPB computer monitor 68.6 cm (27") 1920 x 1080 pixels Full HD LED Touchscreen Black

Gamintojas: **HANNSPREE** · Modelis: **HT279PPB** · EAN: **4711404024917** · Prekės kodas: **703730**



396,90 €

Kaina su PVM

Be PVM: **328,02 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Tilt Angle: 15° ~ 70°
- ✓ 1920 x 1080 Full HD Resolution
- ✓ USB 3.0 HUB
- ✓ HDMI + DP Inputs
- ✓ Edge to Edge Glass Design
- ✓ Ergonomic Smart adjustable stand
- ✓ 10 Points P-Cap Touch
- ✓ 27" 16:9 LED Backlight Monitor
- ✓ Optical Bonding
- ✓ Wall Mountable (VESA)



Aprašymas

Step into a new dimension of interactive display with our 27" Full HD Touch Monitor. Featuring ultra-responsive 10-point P-Cap touch technology and crystal-clear 1920 × 1080 resolution, this display is designed for smooth performance and vibrant visuals. The edge-to-edge glass with optical bonding (OGS) delivers a sleek, modern look while minimizing reflections, and the wide 178° viewing angle ensures consistent clarity from every perspective. Equipped with HDMI and DP inputs, a USB 3.0 hub, integrated stereo speakers, VESA mount compatibility, and a flexible book-stand (15°–70° tilt), this display adapts effortlessly to any environment—from retail settings to creative.

Seamless Touch, Endless Possibilities

Empower teams to play, create, and collaborate with PCAP technology supporting 10-point multi-touch functionality. Enjoy effortless annotation,

smooth navigation, and precise control with intuitive tap, swipe, slide, and pinch gestures. A durable glass overlay ensures reliable performance, resistant to dirt, dust, condensation, liquid spills, and cleaning solutions—making it the perfect choice for everyday, long-lasting use.

Crystal-Clear Precision with Optical Bonding

Experience exceptional clarity and responsiveness with Optical Bonding Technology in our HANNspree HT249PPB and HT279PPB Touch Monitors. By eliminating the air gap between the touch panel and display, this advanced bonding process reduces glare and reflections, enhances contrast, and increases durability. The result? Vivid visuals and an ultra-responsive touch experience with superior accuracy—perfect for professional applications, gaming, and interactive environments. See the difference. Feel the precision. Elevate your touch experience today.

Multi-Touch Screen with 7H Surface Hardness

A 7H scratch-resistant surface ensures durability and a consistently high-quality touch experience. Scratch resistance is essential for touch solutions in education and public environments. A toughened glass overlay protects the screen, allowing the panel surface to withstand scratches and impacts from everyday objects—making it ideal for public spaces and educational institutions.

With its 7H hardness rating, the HT249PPB / HT279PPB is engineered for schools, colleges, universities, as well as retail and industrial applications—delivering long-lasting protection against impacts, dirt, and daily wear.

Speakers and Headphones

The monitor is equipped with built-in stereo speakers that deliver clear, high-quality audio for an enhanced listening experience—ideal for multimedia content in classrooms, presentations, or everyday use. The true stereo effect eliminates the need for external speakers in many situations.

Prefer a more private setup? Simply plug your headset into the headphone jack and enjoy your content without disturbing others.

VESA mount and a flexible book-stand

The included smart adjustable stand of the HT279PPB offers a tilt range of 15° to 70°, allowing you to effortlessly adjust to your ideal viewing angle while minimizing strain on your posture and wrists.

For added versatility, the hinged stand enables the monitor to lie flat on a desk, transforming it into a large tablet. The monitor is also VESA-compatible, making it simple to mount on monitor arms or walls—perfect for maximizing space while enjoying its stunning picture quality, responsive touch interaction, and versatile use in classrooms, retail, or professional environments.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Monitore > Monitore (TFT, LCD, LED) [+1779][-139]
Display	
Display diagonal	68.6 cm (27")
Display resolution	1920 x 1080 pixels
Native aspect ratio	16:9
Display technology	LED
Touchscreen	Yes
HD type	Full HD
Panel type	ADS
Response time	5 ms

Screen shape	Flat
Contrast ratio (typical)	1000:1
Maximum refresh rate	75 Hz
Display number of colours	16.78 million colours
LED backlight	Yes
Backlight type	W-LED
Touchscreen technology	Capacitive
Touch technology	Multi-touch
Number of simultaneous touchpoints	10
Display brightness (peak)	400 cd/m²
Display brightness (typical)	360 cd/m²
Anti-glare screen	Yes
Supported graphics resolutions	1920 x 1080 (HD 1080)
Supported video modes	1080p
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.2745 x 0.2745 mm
Horizontal scan range	30 - 83 kHz
Vertical scan range	50 - 76 Hz
Display diagonal (metric)	68.5 cm
Surface hardness	7H
Colour depth	8 bit
Performance	
Game mode	Yes
Smart modes	Cinema, Game, Standard
Multimedia	
Built-in speaker(s)	Yes
Number of speakers	2
RMS rated power	4 W
Design	
Product colour	Black
Ports & interfaces	
HDMI	Yes
Headphone out	Yes

USB Type-A downstream ports quantity	1
USB Type-B downstream ports quantity	1
USB Touch port	Yes
USB Touch ports quantity	1
HDMI ports quantity	1
HDMI version	1.4
DisplayPorts quantity	1
DisplayPort version	1.2
Audio input	Yes
Headphone outputs	1
Headphone connectivity	3.5 mm

Ergonomics

VESA mounting	Yes
Cable lock slot	Yes
Panel mounting interface	100 x 100 mm
Cable lock slot type	Kensington
Tilt adjustment	Yes
Tilt angle range	15 - 70°
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, German, Dutch, English, Spanish, Finnish, French, Italian, Japanese, Korean, Polish, Portuguese, Russian
Number of OSD languages	15
LED indicators	Yes

Power

Energy efficiency class (SDR)	D
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	15 kWh
Power consumption (typical)	40 W
Power consumption (standby)	0.3 W
Power consumption (off)	0.2 W
AC input voltage	90 - 264 V
Power supply type	Internal
Energy efficiency scale	A to G

Operational conditions

Operating temperature (T-T)	20 - 30 °C
-----------------------------	------------

Operating relative humidity (H-H)	10 - 90%
-----------------------------------	----------

Weight & dimensions

Width (with stand)	614.1 mm
--------------------	----------

Depth (with stand)	367.8 mm
--------------------	----------

Height (with stand)	480.9 mm
---------------------	----------

Weight (with stand)	5.8 kg
---------------------	--------

Packaging data

Package width	710 mm
---------------	--------

Package depth	460 mm
---------------	--------

Package height	130 mm
----------------	--------

Package weight	7.3 kg
----------------	--------

Packaging content

Cables included	AC, HDMI, USB Type-A to USB Type-B
-----------------	------------------------------------

Power adapter included	Yes
------------------------	-----

Quick start guide	Yes
-------------------	-----

Manual	Yes
--------	-----

Sustainability

Sustainability certificates	ErP
-----------------------------	-----

Other features

Compliance certificates	CE, RoHS
-------------------------	----------

Matmenys ir svoris

Svoris	7,30kg
--------	--------