

ASUS Dual -RX9060XT-16G AMD Radeon RX 9060 XT 16 GB GDDR6

Gamintojas: **ASUS** · Modelis: **90YV0LG2-M0NA00** · EAN: **4711636196765** · Prekės kodas: **704768**



757,90 €

Kaina su PVM

Be PVM: **626,36 €**

Sandėlyje



Prekė internetu

Nuskuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ AMD Radeon RX 9060 XT 16 GB GDDR6
- ✓ 7680 x 4320 pikseliai 128 bitai 20 Gbit/s PCI Express 5.0
- ✓ HDMI portų kiekis: 1 „DisplayPort“ kiekis: 2
- ✓ „DirectX“ versija: 12 Ultimate OpenGL versija: 4.6
- ✓ 1x 8-pin



Aprašymas

Dual Radeon™ RX 9060 XT

Dual Fans, Perfect Fit

ASUS Dual Radeon™ RX 9060 XT combines powerful thermal performance with broad compatibility. Advanced cooling solutions from flagship graphics cards — including two Axial-tech fans for optimizing airflow to the heatsink. Designed in a compact 2.5-slot form factor, delivering more power in less space. These enhancements make ASUS Dual the perfect choice for gamers who want heavyweight graphics performance in a compact build.

Cooling

2.5-slot Design

A carefully designed shroud, heatsink, and heatpipe layout enables the two Axial-tech fans to leverage chassis side-panel ventilation, delivering thermal performance that beyond the compact size.

Axial-tech Upgrades

Two tried-and-true Axial-tech fans feature a smaller hub facilitates longer blades and a barrier ring to increase downward air pressure.

0dB Technology

To eliminate unnecessary noise, the stop mode automatically halts all fans when the GPU temperature drops below 55°C and power consumption is low.

Dual Ball Fan Bearings

Fan bearings come in different types, each with its own advantages. Dual ball bearings provide superior durability and can last up to twice as long as sleeve-bearing designs.

Vented Backplate

A vented backplate significantly enhances heat dissipation, helping to keep the GPU cooler during intense tasks. This additional airflow helps ensure optimal temperatures, boosting performance, longevity and stability by defending against overheating and thermal throttling.

Unmatched Reliability

ASUS GPU Guard

ASUS GPU Guard applies adhesive to secure all four corners to reduce the risk of cracks.

Protective Backplate

The PCB is reinforced by a backplate that adds structural rigidity, helping to prevent flex and to protect components and trace pathways from damage.

Stainless Steel Bracket

The mounting bracket of the Dual has been beefed up with 304 Stainless Steel that's harder and more resistant to corrosion.

Engineering

Dual BIOS

Do you prioritize lower core temperatures or quieter operation? Performance mode increases fan speed to keep the card running cool all the time. Quiet mode maintains the same power target and performance settings, but applies a less aggressive fan curve for quieter operation at medium temperatures. Want more control? Customize your experience with GPU Tweak III software for fine-tuned fan profiles and performance adjustments.

Auto–Extreme Technology

Auto-Extreme Technology is an automated manufacturing process that sets new standards in the industry by allowing completing all soldering to be completed in a single pass. This reduces thermal strain on components and avoids the use of harsh cleaning chemicals, resulting and minimizes in less environmental impact. The result is lower power consumption during manufacturing and a more reliable, high-quality product.lower manufacturing power consumption, and a more reliable product overall.

Techninė specifikacija

Procesorius	
Grafikos procesoriaus šeima	AMD
Grafikos procesorius	Radeon RX 9060 XT
Maksimali rezoliucija	7680 x 4320 pikseliai
CUDA	Ne
Paralelinio apdorojimo technologijos parama	Nepalaikomas
Procesoriaus laikrodžio greičio padidinimas	3230 MHz
Procesoriaus spartinimo laikrodžio greitis (OC režimas)	3250 MHz
Procesoriaus paspartintas taktinis dažnis (žaidimų režimas)	2640 MHz
Srauto procesoriai	2048
Maksimalus ekranų skaičius kiekvienai vienai vaizdo plokštei	3
Atmintis	
Diskrečiojo grafikos adapterio atmintis	16 GB
Grafikos adapterio atminties tipas	GDDR6
Atminties magistralė	128 bitai
Duomenų perdavimo sparta	20 Gbit/s
Ryšys	
Sąsajos tipas	PCI Express 5.0
HDMI portų kiekis	1
DVI-D prievadų skaičius	0
DVI-I prievadų skaičius	0
„DisplayPort“ kiekis	2
3 „Thunderbolt“ prievadų skaičius	0
Mini HDMI portų kiekis	0
HDMI versija	2.1b
VGA (D-Sub) portų kiekis	0
„Mini DisplayPort“ kiekis	0
„DisplayPort“ versija	2.1a
USB tipo C prievadų kiekis	0

Veikimo charakteristikos

Integruotas TV tiuneris	Ne
„DirectX“ versija	12 Ultimate
OpenGL versija	4.6
Dvi DVI išvestys	Ne
HDCP	Taip
HDCP versija	2.3

Konstrukcija

Aušinimo tipas	Aktyvus
Aušinimo technologija	ASUS Axial-tech
Ventiliatorių skaičius	2 ventiliatorius(iai / ių)
Forma	Full-Height/Half-Length (FH/HL)
Laikiklio aukštis	Full-Height (FH)
Lizdų skaičius	2,5
Iliuminacija	Ne
Suderinama su SFF standartu	Taip
Produkto spalva	Juoda

Energijos valdymas

Minimalus sistemos maitinimas	550 W
Papildomos maitinimo jungtys	1x 8-pin

Sistemos reikalavimai

Palaikomos „Windows“ operacinės sistemos	Windows 10 x64, Windows 11 x64
--	--------------------------------

Svoris ir matmenys

Ilgis	202 mm
Ilgis	49 mm
Aukštis	120 mm

Pakuotės duomenys

Pakuotės tipas	„Box“
----------------	-------

Pakuotės turinys

Instrukcija	Taip
-------------	------

Matmenys ir svoris

Matmenys (I × P × A)	37,00cm × 22,00cm × 7,00cm
Svoris	1,09kg

Dokumentai ir vaizdo įrašai

> [Naudojimo instrukcija](#)

Gamintojo ir saugos informacija

GAMINTOJAS

ASUSTeK Computer Inc

Li-Te Road 15, 112 Taipei, TW

[asus.com](https://www.asus.com)

ATSAKINGAS ASMUO ES

ASUS France S.A.R.L.

Allee bienvenue 10, 93160 Paris, FR

channel.asus.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt