

Hannspree HO 325 PTB computer monitor 80 cm (31.5") 1920 x 1080 pixels Full HD LED Touchscreen Black

Gamintojas: **HANNSPREE** · Modelis: **HO325PTB** · EAN: **4711404023002** · Prekės kodas: **706499**



722,90 €

Kaina su PVM

Be PVM: **597,44 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 1920 x 1080 Full HD 1080P Resolution
- ✓ 10-Point Touch P-Cap Technology
- ✓ 178° / 178° Ultra Wide Viewing Angle
- ✓ 400 cd/m² High Brightness Panel
- ✓ Video Input: HDMI + Display Port
- ✓ IP55 (front) Rating Level
- ✓ Display Protection: Thickness 3mm
- ✓ Built-in Speakers
- ✓ ≥7H Toughened Hard Panel Surface
- ✓ Slim Profile, Edge-to-Edge True Flat Surface



Aprašymas

The HANNspree HO325PTB 32" 16:9 Open-Frame monitor delivers a high-performance display solution. Its rugged bezel with edge-to-edge glass makes it very suitable for applications like tabletop integration.

The HANNspree HO325PTB is an ideal display for integration in kiosk, totem and a perfect solution for interactive digital signage, In-store Retail, Gaming and many other sectors.

LIMITLESS POSSIBILITIES WITH OPEN FRAME

Designed for demanding environments, the HANNSpree Open Frame series delivers a long life cycle, high resolution experience to a wide range of commercial and industrial applications. Featuring a molded metal casing to extra protection, these open-frame monitors have a long-lasting product life cycle, Digital video inputs along with VESA and or flange mount capability on selected models, the HANNSpree Industrial Open-Frame family make the most of your digital world.

Choose from standard or touch screen high performance displays ranging from 10.1" up to 55" and the right aspect ratio to best fit your application.

TOUCH-THROUGH GLASS

Now multiple users can experience shared touchscreen interaction. Using up to 10 finger touchpoints, the HANNSpree HO325PTB Monitor allows everyone to play and collaborate at the same time.

The precise and accurate multi-touch display — allowing up to 10 simultaneous touches — allowing you to work smarter and more efficiently.

There's no need for additional controllers – all they have to do is just reach out and touch the screen. It is certified for Windows 10 and designed to offer superior performance as well as intuitive control, so you can be more productive and do everything you want to do smoothly and quickly.

With Projected Capacitive Touch, users can enjoy a smoother and more accurate touch display experience with increased interactivity. Thanks to the glass overlay this technology is highly durable, the Touch performance is unaffected by everyday use and mishaps such as dirt, dust, condensation, liquid spills or cleaning solutions.

This technology delivers super-fast, sensitive touch response with excellent dragging performance and perfect picture quality. Ten-point multi-touch support lets you unlock the power of today's touch-enabled applications.

MOUNTING OPTIONS

Its rugged bezel with edge-to-edge glass makes it very suitable for applications like tabletop integration. The display supports rear VESA and external mounting brackets for multiple mounting options. The brackets provide the benefits of easy installation and flexibility for different applications.

- Supports Multiple Mounting Options
- Slim profile with narrow edges

VIVID IMAGES, LIFELIKE VISUALS WITH ULTRA-WIDE VIEWING ANGLES

The Touch monitor HO325PTB features a 16:9 aspect ratio LED-backlit panel with a 178° ultra-wide view angle that minimizes colour shift on both horizontal and vertical planes to ensure quality visuals from almost any direction. It delivers improved colour accuracy plus increased energy efficiency.

The HO325PTB uses a 178°(H) / 178°(V) ultra-wide viewing angle Full HD panel that eliminates colour shift from almost any direction and in nearly every angle.

SCRATCH-RESISTANT - MULTI-TOUCH SCREEN WITH 7H SURFACE HARDNESS

7H scratch resistant surface hardness ensures durability, as well as a consistent high-quality touch experience.

Scratch resistance is essential for touch solutions used for education and public environment. This is achieved thanks to a glass overlay covering the screen. This means that the panel surface can withstand impact from objects and scratches, making it perfect for public spaces and educational institutions.

Our toughened Hard Glass fronted LED Monitors (7H hardness rating) are designed specifically for retail and Industrial applications offering protection from impacts and dirt for a long-life solution.

It guarantees high durability of the touch function and even more importantly the touch function remains unaffected even if the glass is scratched.

CONNECTIVITY

The HANNspree HO325PTB features a host of connectivity options that include VGA, HDMI and DP.

The HO325PTB Open Frame Touch Monitor ensures that your monitor is more compatible and ready to handle all of your content.

Enabling touch is easy! Simply connect the USB cable from your PC to the monitor's USB upstream port, and connect one of the video inputs to project images onscreen.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Monitore > Monitore (TFT, LCD, LED) [+1779][-139]
Display	
Display diagonal	80 cm (31.5")
Display resolution	1920 x 1080 pixels
Native aspect ratio	16:9
Display technology	LED
Touchscreen	Yes
HD type	Full HD
Panel type	TFT
Response time	8 ms
Screen shape	Flat
Contrast ratio (typical)	1200:1
Maximum refresh rate	60 Hz
Display number of colours	16.78 million colours
LED backlight	Yes
Backlight type	LED
Touchscreen technology	Projected capacitive system
Touch technology	Multi-touch
Number of simultaneous touchpoints	10
Display brightness (typical)	400 cd/m²
Display brightness	400 cd/m²
Contrast ratio (dynamic)	10000000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.364 x 0.364 mm

Horizontal scan range	31 - 83 kHz
Vertical scan range	56 - 75 Hz
Viewable size, horizontal	69.8 cm
Viewable size, vertical	39.3 cm
Display diagonal (metric)	80 cm
Surface hardness	7H
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Multimedia	
Built-in speaker(s)	Yes
Built-in camera	No
Number of speakers	2
RMS rated power	2 W
Built-in microphone	No
Design	
Market positioning	Business
Product colour	Black
Housing material	Metal
Glass thickness	3 mm
Ports & interfaces	
HDMI	Yes
USB 3.2 Gen 1 (3.1 Gen 1) Type-B ports quantity	1
HDMI ports quantity	1
DisplayPorts quantity	1
Audio input	Yes
Audio output	Yes
Ergonomics	
VESA mounting	Yes
Panel mounting interface	100 x 100 mm
Wall mountable	Yes
On Screen Display (OSD)	Yes
Number of OSD languages	15
Power	

Energy efficiency class (SDR)	E
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	25 kWh
Power consumption (typical)	40 W
Power consumption (standby)	0.5 W
Power consumption (max)	45 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50 / 60 Hz
Power supply type	AC
Energy efficiency scale	A to G
Weight & dimensions	
Width (without stand)	747 mm
Depth (without stand)	451.4 mm
Height (without stand)	64.3 mm
Weight (without stand)	14.5 kg
Packaging data	
Package width	863 mm
Package depth	163 mm
Package height	577 mm
Package weight	16.8 kg
Packaging content	
Cables included	AC, HDMI, USB
Quick start guide	Yes
Other features	
International Protection (IP) code	IP55
Compliance certificates	RoHS
Certification	CE
Logistics data	
Harmonized System (HS) code	85285210
Matmenys ir svoris	
Svoris	15,10kg